



Commercial Lighting



Industrial Lighting



Sports Lighting

MLLG-AG-LED-HPSL Flood Light Product Family



**Why
contractors
choose us**



Free Lighting
Plans to ensure
customer
satisfaction



Dedicated
Lighting
Specialist for
each project



Large
inventory of
LED Lights

Table of Contents

	Page Number
- MLLG-LED-HPSL-400-57-60	3
- MLLG-LED-HPSL-400-57-60-MG	4
- MLLG-LED-HPSL-600-57-60	5
- MLLG-LED-HPSL-600-57-60-MG	6
- MLLG-LED-HPSL-800-57-60	7
- MLLG-LED-HPSL-960-57-60	8
- MLLG-LED-HPSL-1200-57-60	9

400 Watt LED Stadium Light | 60000 Lumens | 5700K | 100-277V



Product Details

SKU: MLLG-LED-HPSL-400-57-60

Web ID: 2092

400 Watt high power flood light - sport light produces 60000 lumens at 150 lumens/watt replacing 1000 Watt Metal Halide. Aluminum lighting modules can be adjusted individually. All fixtures are equipped with a 0-10V dimmable driver and built-in 20kVA surge protection.

It comes with a 100V-277V or 277V-480V Optional LED Driver 3000K or 4000K or 5700K color temperatures and a 60 standard beam angle. This fixture has a Trunnion-style mount. The driver for the fixture can be mounted on the light bracket or remotely on or inside the pole. Visors and an optional precision aiming laser are also available.

They are Wet Location IP66 rated and High Impact IK08 rated and can operate in temperatures ranging from -22 F to 122 F.

Optional Configurations:

Beam Angles: 10 30 45 T3 (60 standard)

High Voltage: 277-480V (100-277V standard)

Color Temperature: 3000K & 4000K (5700K standard)

Precision Aiming Laser

Light Visor

Product Specifications

Watts:	400	Dimmable:	0-10V
Lumens:	60000	Beam Angle:	60°(std), 10°, 30°, 45°, T3
Lumens/Watt:	150	Optics:	Polycarbonate Lens
Replaces:	1000 Watt Metal Halide	Frequency:	50/60 hz
Color Temp:	3000K 4000K 5700K	Power Factor:	.97
CRI:	80+	Housing:	Powder Coated Aluminum
IP Rating:	IP66	Fixture Color:	Black
IK Rating:	IK08	Mounting:	Trunnion
Input Voltage:	100V-277V 277V-480V Optional	EPA Rating:	0.96
Surge Protection:	10KV line-line, 20KV line-earth	Dimensions:	18.8 in W in X 11.2 in H X 7.3 in D
Operating Temp:	-22°F to +122°F	Weight:	Fixture body 14 lbs Driver Box 8 lbs
Rated Life:	200,000 (L70) hours	Warranty:	5 years

Product Options

Visor

Visor

400 Watt LED Stadium Light | 60000 Lumens | 5700K | 100-277V



Product Details

SKU: MLLG-LED-HPSL-400-57-60-MG

Web ID: 2149

400 Watt high power flood light - marine grade light produces 60000 lumens at 150 lumens/watt replacing 1000 Watt Metal Halide. Aluminum lighting modules can be adjusted individually. All fixtures are equipped with a 0-10V dimmable driver and built-in 20kVA surge protection.

It comes with a 100V-277V LED Driver 5700K color temperatures and a 60 standard beam angle. This fixture has a Trunnion-style mount. The driver for the fixture can be mounted on the light bracket or remotely on or inside the pole. Visors and an optional precision aiming laser are also available.

They are Wet Location IP66 rated and High Impact IK08 rated and can operate in temperatures ranging from -22 F to 122 F.

Meets ISO 12944 C4 Marine Grade Specification.

Optional Configurations:

Beam Angles: 10 30 45 T3 (60 standard)

High Voltage: 277-480V (100-277V standard)

Color Temperature: 3000K & 4000K (5700K standard)

Precision Aiming Laser

Light Visor

Product Specifications

Watts:	400	Dimmable:	0-10V
Lumens:	60000	Beam Angle:	60°(std), 10°, 30°, 45°, T3
Lumens/Watt:	150	Optics:	Polycarbonate Lens
Replaces:	1000 Watt Metal Halide	Frequency:	50/60 hz
Color Temp:	5700K	Power Factor:	.97
CRI:	80+	Housing:	ISO 12944 C4 Marine Grade
IP Rating:	IP66	Fixture Color:	Black
IK Rating:	IK08	Mounting:	Trunnion
Input Voltage:	100V-277V	EPA Rating:	0.96
Surge Protection:	10KV line-line, 20KV line-earth	Dimensions:	18.8 in W in X 11.2 in H X 7.3 in D
Operating Temp:	-22°F to +122°F	Weight:	Fixture body 14 lbs Driver Box 8 lbs
Rated Life:	200,000 (L70) hours	Warranty:	5 years

600 Watt LED Stadium Light | 90000 Lumens | 5700K | 100-277V



Product Details

SKU: MLLG-LED-HPSL-600-57-60

Web ID: 2093

600 Watt high power flood light - sport light produces 90000 lumens at 150 lumens/watt replacing 1500 Watt Metal Halide. Aluminum lighting modules can be adjusted individually. All fixtures are equipped with a 0-10V dimmable driver and built-in 20kVA surge protection.

It comes with a 100V-277V or 277V-480V Optional LED Driver 3000K or 4000K or 5700K color temperatures and a 60 standard beam angle. This fixture has a Trunnion-style mount. The driver for the fixture can be mounted on the light bracket or remotely on or inside the pole. Visors and an optional precision aiming laser are also available.

They are Wet Location IP66 rated and High Impact IK08 rated and can operate in temperatures ranging from -22 F to 122 F.

Optional Configurations:

Beam Angles: 10 30 45 T3 (60 standard)

High Voltage: 277-480V (100-277V standard)

Color Temperature: 3000K & 4000K (5700K standard)

Precision Aiming Laser

Light Visor

Product Specifications

Watts:	600	Dimmable:	0-10V
Lumens:	90000	Beam Angle:	60°(std), 10°, 30°, 45°, T3
Lumens/Watt:	150	Optics:	Polycarbonate Lens
Replaces:	1500 Watt Metal Halide	Frequency:	50/60 hz
Color Temp:	3000K 4000K 5700K	Power Factor:	.97
CRI:	80+	Housing:	Powder Coated Aluminum
IP Rating:	IP66	Fixture Color:	Black
IK Rating:	IK08	Mounting:	Trunnion
Input Voltage:	100V-277V 277V-480V Optional	EPA Rating:	1.34
Surge Protection:	10KV line-line, 20KV line-earth	Dimensions:	18.8 in W in X 11.2 in H X 7.3 in D
Operating Temp:	-22°F to +122°F	Weight:	Fixture body 17.2 lbs Driver Box 10.4 lbs
Rated Life:	200,000 (L70) hours	Warranty:	5 years

Product Options

Visor	
Visor	

600 Watt LED Stadium Light | 90000 Lumens | 5700K | 100-277V



Product Details

SKU: MLLG-LED-HPSL-600-57-60-MG

Web ID: 2150

600 Watt high power flood light - marine grade light produces 90000 lumens at 150 lumens/watt replacing 1500 Watt Metal Halide. Aluminum lighting modules can be adjusted individually. All fixtures are equipped with a 0-10V dimmable driver and built-in 20kVA surge protection.

It comes with a 100V-277V LED Driver 5700K color temperatures and a 60 standard beam angle. This fixture has a Trunnion-style mount. The driver for the fixture can be mounted on the light bracket or remotely on or inside the pole. Visors and an optional precision aiming laser are also available.

They are Wet Location IP66 rated and High Impact IK08 rated and can operate in temperatures ranging from -22 F to 122 F.

Meets ISO 12944 C4 Marine Grade Specification.

Optional Configurations:

Beam Angles: 10 30 45 T3 (60 standard)

High Voltage: 277-480V (100-277V standard)

Color Temperature: 3000K & 4000K (5700K standard)

Precision Aiming Laser

Light Visor

Product Specifications

Watts:	600	Dimmable:	0-10V
Lumens:	90000	Beam Angle:	60°(std), 10°, 30°, 45°, T3
Lumens/Watt:	150	Optics:	Polycarbonate Lens
Replaces:	1500 Watt Metal Halide	Frequency:	50/60 hz
Color Temp:	5700K	Power Factor:	.97
CRI:	80+	Housing:	ISO 12944 C4 Marine Grade
IP Rating:	IP66	Fixture Color:	Black
IK Rating:	IK08	Mounting:	Trunnion
Input Voltage:	100V-277V	EPA Rating:	1.34
Surge Protection:	10KV line-line, 20KV line-earth	Dimensions:	18.8 in W in X 11.2 in H X 7.3 in D
Operating Temp:	-22°F to +122°F	Weight:	Fixture body 17.2 lbs Driver Box 10.4 lbs
Rated Life:	200,000 (L70) hours	Warranty:	5 years

800 Watt LED Stadium Light | 120000 Lumens | 5700K | 100-277V



Product Details

SKU: MLLG-LED-HPSL-800-57-60

Web ID: 2009

800 Watt high power flood light - sport light produces 120000 lumens at 150 lumens/watt replacing 1500 Watt Metal Halide. Aluminum lighting modules can be adjusted individually. All fixtures are equipped with a 1-10V dimmable driver and built-in 20kVA surge protection.

It comes with a 100V-277V or 277V-480V Optional LED Driver 3000K or 4000K or 5700K color temperatures and a 60 standard beam angle. This fixture has a Trunnion-style mount. The driver for the fixture can be mounted on the light bracket or remotely on or inside the pole. Visors and an optional precision aiming laser are also available.

They are Wet Location IP66 rated and High Impact IK08 rated and can operate in temperatures ranging from -22 F to 122 F.

Optional Configurations:

Beam Angles: 10 30 45 T3 (60 standard)

High Voltage: 277-480V (100-277V standard)

Color Temperature: 3000K & 4000K (5700K standard)

Precision Aiming Laser

Light Visors

Product Specifications

Watts:	800	Dimmable:	0-10V
Lumens:	120000	Beam Angle:	60°(std), 10°, 30°, 45°, T3
Lumens/Watt:	150	Optics:	Polycarbonate Lens
Replaces:	1500 Watt Metal Halide	Frequency:	50/60 hz
Color Temp:	3000K 4000K 5700K	Housing:	Powder Coated Aluminum (Marine Grade Optional)
CRI:	80+	Fixture Color:	Black
IP Rating:	IP66	Mounting:	Trunnion
IK Rating:	IK08	EPA Rating:	1.92
Input Voltage:	100V-277V 277V-480V Optional	Dimensions:	20 in W in X 17 in H X 9.2 in D
Surge Protection:	10KV line-line, 20KV line-earth	Weight:	Fixture body 30.2 lbs Driver Box 12 lbs
Operating Temp:	-22°F to +122°F	Warranty:	5 years
Rated Life:	200,000 (L70) hours		

960 Watt LED Stadium Light | 144000 Lumens | 5700K | 100-277V



Product Details

SKU: MLLG-LED-HPSL-960-57-60

Web ID: 2010

960 Watt high power flood light - sport light produces 144000 lumens at 150 lumens/watt replacing 1500 Watt Metal Halide. Aluminum lighting modules can be adjusted individually. All fixtures are equipped with a 1-10V dimmable driver and built-in 20kVA surge protection.

It comes with a 100V-277V or 277V-480V Optional LED Driver 3000K or 4000K or 5700K color temperatures and a 60 standard beam angle. This fixture has a Trunnion-style mount. The driver for the fixture can be mounted on the light bracket or remotely on or inside the pole. Visors and an optional precision aiming laser are also available.

They are Wet Location IP66 rated and High Impact IK08 rated and can operate in temperatures ranging from -22 F to 122 F.

Optional Configurations:

Beam Angles: 10 30 45 T3 (60 standard)

High Voltage: 277-480V (100-277V standard)

Color Temperature: 3000K & 4000K (5700K standard)

Precision Aiming Laser

Light Visor

Product Specifications

Watts:	960	Dimmable:	0-10V
Lumens:	144000	Beam Angle:	60°(std), 10°, 30°, 45°, T3
Lumens/Watt:	150	Optics:	Polycarbonate Lens
Replaces:	1500 Watt Metal Halide	Frequency:	50/60 hz
Color Temp:	3000K 4000K 5700K	Housing:	Powder Coated Aluminum (Marine Grade Optional)
CRI:	80+	Fixture Color:	Black
IP Rating:	IP66	Mounting:	Trunnion
IK Rating:	IK08	EPA Rating:	2.3
Input Voltage:	100V-277V 277V-480V Optional	Dimensions:	20 in W in X 21 in H X 11.3 in D
Surge Protection:	10KV line-line, 20KV line-earth	Weight:	Fixture body 36 lbs Driver Box 14.5 lbs
Operating Temp:	-22°F to +122°F	Warranty:	5 years
Rated Life:	200,000 (L70) hours		

1200 Watt LED Stadium Light | 180000 Lumens | 5700K | 100-277V



Product Details

SKU: MLLG-LED-HPSL-1200-57-60

Web ID: 2011

1200 Watt high power flood light - sport light produces 180000 lumens at 150 lumens/watt replacing 2000 Watt Metal Halide. Aluminum lighting modules can be adjusted individually. All fixtures are equipped with a 1-10V dimmable driver and built-in 20kVA surge protection.

It comes with a 100V-277V or 277V-480V Optional LED Driver 3000K or 4000K or 5700K color temperatures and a 60 standard beam angle. This fixture has a Trunnion-style mount. The driver for the fixture can be mounted on the light bracket or remotely on or inside the pole. Visors and an optional precision aiming laser are also available.

They are Wet Location IP66 rated and High Impact IK08 rated and can operate in temperatures ranging from -22 F to 122 F.

Optional Configurations:

Beam Angles: 10 30 45 T3 (60 standard)

High Voltage: 277-480V (100-277V standard)

Color Temperature: 3000K & 4000K (5700K standard)

Precision Aiming Laser

Light Visor

Product Specifications

Watts:	1200	Dimmable:	0-10V
Lumens:	180000	Beam Angle:	60°(std), 10°, 30°, 45°, T3
Lumens/Watt:	150	Optics:	Polycarbonate Lens
Replaces:	2000 Watt Metal Halide	Frequency:	50/60 hz
Color Temp:	3000K 4000K 5700K	Housing:	Powder Coated Aluminum (Marine Grade Optional)
CRI:	80+	Fixture Color:	Black
IP Rating:	IP66	Mounting:	Trunnion
IK Rating:	IK08	EPA Rating:	2.68
Input Voltage:	100V-277V 277V-480V Optional	Dimensions:	20 in W in X 22.5 in H X 11.3 in D
Surge Protection:	10KV line-line, 20KV line-earth	Weight:	Fixture body 42 lbs Driver Box 14.5 lbs
Operating Temp:	-22°F to +122°F	Warranty:	5 years
Rated Life:	200,000 (L70) hours		