



Commercial Lighting



Industrial Lighting



Sports Lighting

MLLG-AG-LED-IMF Flood Light Product Family



**Why
contractors
choose us**



Free Lighting
Plans to ensure
customer
satisfaction



Dedicated
Lighting
Specialist for
each project



Large
inventory of
LED Lights

Table of Contents

	Page Number
- MLLG-AG-LED-IMF-200-5-[Optic]-TR-[V]	3
- MLLG-AG-LED-IMF-400-5-[Optic]-TR-[V]	4
- MLLG-AG-LED-IMF-600-5-[Optic]-TR-[V]	5
- MLLG-AG-LED-IMF-200-5-60-TR-MG	6
- MLLG-AG-LED-IMF-400-5-60-TR-MG	7

200 Watt LED Area Flood Light | 28000 Lumens | 5000K | 100V-277V or 277V-480V



Product Details

SKU: MLLG-AG-LED-IMF-200-5-[Optic]-TR-[V]

Web ID: 1653

200 Watt flood light - sport light produces 28000 lumens at 140 lumens/watt. The high energy efficiency of these lights will provide significant energy savings compared to metal halide and halogen bulbs. This LED fixture is an ideal replacement for existing 400 Watt Metal Halide lights when being energy efficient is a priority.

Aluminum lighting modules can be adjusted individually. All fixtures are equipped with a 1-10V dimmable driver and built-in 10KvA surge protection to enhance the durable construction of the unit. The perfect solution for outdoor projects such as perimeter security lighting parking lot lighting sports fields and other commercial lighting applications.

The fixtures come standard with a 100V-277V or 277V-480V LED Driver to power the LED chips and come available in 4000K or 5000K color temperature. 60 (std) 10 15 30 45 beam angle comes standard for ideal luminous flux. 10 15 30 45 40 100 beam angles are available. This fixture has several different mounting options including Slip Fitter or Trunnion for near-universal mounting options for every area from building facades to parking lots.

These fixtures are wet location IP66 and High Impact IK08 Rated and can operate from -22 F to 113 F.

Product Specifications

Watts:	200	Dimmable:	1-10V
Lumens:	28000	Beam Angle:	60°(std), 10°, 15°, 30°, 45°
Lumens/Watt:	140	Optics:	Polycarbonate Optics and Tempered Glass Lens
Replaces:	400 Watt Metal Halide	Frequency:	50/60 hz
Color Temp:	4000K 5000K	Housing:	Powder Coated Aluminum
CRI:	70+	Fixture Color:	Gray
IP Rating:	IP66	Mounting:	Slip Fitter Trunnion
IK Rating:	IK08	EPA Rating:	1.36
Input Voltage:	100V-277V 277V-480V	Dimensions:	12.64 in X 12.44 in X 4.65 in
Surge Protection:	6kV line-line, 10kV line-earth	Weight:	13 lbs
Operating Temp:	-22°F to +113°F	Warranty:	5 years
Rated Life:	176,000 (L70) hours		

Product Options

Mount	Visor
Trunnion Bracket Mount Slipfitter Mount	Visor Kit

400 Watt LED Area Flood Light | 56000 Lumens | 5000K | 100V-277V or 277V-480V



Product Details

SKU: MLLG-AG-LED-IMF-400-5-[Optic]-TR-[V]

Web ID: 1654

400 Watt flood light - sport light produces 56000 lumens at 140 lumens/watt. The high energy efficiency of these lights will provide significant energy savings compared to metal halide and halogen bulbs. This LED fixture is an ideal replacement for existing 1000 Watt Metal Halide lights when being energy efficient is a priority.

Aluminum lighting modules can be adjusted individually. All fixtures are equipped with a 1-10V dimmable driver and built-in 10KvA surge protection to enhance the durable construction of the unit. The perfect solution for outdoor projects such as perimeter security lighting parking lot lighting sports fields and other commercial lighting applications.

The fixtures come standard with a 100V-277V or 277V-480V LED Driver to power the LED chips and come available in 4000K or 5000K color temperature. 60 (std) 10 15 30 45 beam angle comes standard for ideal luminous flux. 10 15 30 45 40 100 beam angles are available. This fixture has several different mounting options including Slip Fitter or Trunnion for near-universal mounting options for every area from building facades to parking lots.

These fixtures are wet location IP66 and High Impact IK08 Rated and can operate from -22 F to 113 F.

Product Specifications

Watts:	400	Dimmable:	1-10V
Lumens:	56000	Beam Angle:	60°(std), 10°, 15°, 30°, 45°
Lumens/Watt:	140	Optics:	Polycarbonate Optics and Tempered Glass Lens
Replaces:	1000 Watt Metal Halide	Frequency:	50/60 hz
Color Temp:	4000K 5000K	Housing:	Powder Coated Aluminum
CRI:	70+	Fixture Color:	Gray
IP Rating:	IP66	Mounting:	Slip Fitter Trunnion
IK Rating:	IK08	EPA Rating:	1.89
Input Voltage:	100V-277V 277V-480V	Dimensions:	18.82 in X 10.63 in X 15.35 in
Surge Protection:	6kV line-line, 10kV line-earth	Weight:	24 lbs
Operating Temp:	-22°F to +113°F	Warranty:	5 years
Rated Life:	176,000 (L70) hours		

Product Options

Mount	Visor
Trunnion Bracket Mount Slipfitter Mount	Visor Kit

600 Watt LED Flood Light | 84000 Lumens | 5000K | 100V-277V or 277V-480V



Product Details

SKU: MLLG-AG-LED-IMF-600-5-[Optic]-TR-[V]

Web ID: 1655

600 Watt flood light - sport light produces 84000 lumens at 140 lumens/watt. The high energy efficiency of these lights will provide significant energy savings compared to metal halide and halogen bulbs. This LED fixture is an ideal replacement for existing 1500 Watt Metal Halide lights when being energy efficient is a priority.

Aluminum lighting modules can be adjusted individually. All fixtures are equipped with a 1-10V dimmable driver and built-in 10KvA surge protection to enhance the durable construction of the unit. The perfect solution for outdoor projects such as perimeter security lighting parking lot lighting sports fields and other commercial lighting applications.

The fixtures come standard with a 100V-277V or 277V-480V LED Driver to power the LED chips and come available in 4000K or 5000K color temperature. 60 (std) 10 15 30 45 beam angle comes standard for ideal luminous flux. 10 15 30 45 40 100 beam angles are available. This fixture has several different mounting options including Slip Fitter or Trunnion for near-universal mounting options for every area from building facades to parking lots.

These fixtures are wet location IP66 and High Impact IK08 Rated and can operate from -22 F to 113 F.

Product Specifications

Watts:	600	Dimmable:	1-10V
Lumens:	84000	Beam Angle:	60°(std), 10°, 15°, 30°, 45°
Lumens/Watt:	140	Optics:	Polycarbonate Optics and Tempered Glass Lens
Replaces:	1500 Watt Metal Halide	Frequency:	50/60 hz
Color Temp:	4000K 5000K	Housing:	Powder Coated Aluminum
CRI:	70+	Fixture Color:	Gray
IP Rating:	IP66	Mounting:	Slip Fitter Trunnion
IK Rating:	IK08	EPA Rating:	2.3
Input Voltage:	100V-277V 277V-480V	Dimensions:	20.83 in X 13.39 in X 8.9 in
Surge Protection:	6kV line-line, 10kV line-earth	Weight:	38 lbs
Operating Temp:	-22°F to +113°F	Warranty:	5 years
Rated Life:	176,000 (L70) hours		

Product Options

Mounting	Visor
Trunnion Bracket Mount Slipfitter Mount	Visor Kit

200 Watt LED Flood Light | 28000 Lumens | 5000K | 100V-277V | Marine Grade



Product Details

SKU: MLLG-AG-LED-IMF-200-5-60-TR-MG

Web ID: 2147

200 Watt flood light marine grade produces 28000 lumens at 140 lumens/watt. The high energy efficiency of these lights will provide significant energy savings compared to metal halide and halogen bulbs. This LED fixture is an ideal replacement for existing 400 Watt Metal Halide lights when being energy efficient is a priority.

Aluminum lighting modules can be adjusted individually. All fixtures are equipped with a 1-10V dimmable driver and built-in 10KvA surge protection to enhance the durable construction of the unit. The perfect solution for outdoor projects such as perimeter security lighting container ship lighting marine vessel lighting and others.

Meets ISO 12944 C4 Marine Grade SpecificationThe fixtures come standard with a 100V-277V LED Driver to power the LED chips and come available in 5000K color temperature. 60 (std) 10 15 30 45 beam angle comes standard for ideal luminous flux. 10 15 30 45 40 100 beam angles are available. This fixture has several different mounting options including Slip Fitter or Trunnion for near-universal mounting options.

These fixtures are wet location IP66 and High Impact IK08 Rated and can operate from -22 F to 113 F.

Product Specifications

Watts:	200	Dimmable:	1-10V
Lumens:	28000	Beam Angle:	60°(std), 10°, 15°, 30°, 45°
Lumens/Watt:	140	Optics:	Polycarbonate Optics and Tempered Glass Lens
Replaces:	400 Watt Metal Halide	Frequency:	50/60 hz
Color Temp:	5000K	Housing:	ISO 12944 C4 Marine Grade
CRI:	70+	Fixture Color:	Gray
IP Rating:	IP66	Mounting:	Slip Fitter Trunnion
IK Rating:	IK08	EPA Rating:	1.36
Input Voltage:	100V-277V	Dimensions:	12.64 in X 12.44 in X 4.65 in
Surge Protection:	6kV line-line, 10kV line-earth	Weight:	13 lbs
Operating Temp:	-22°F to +113°F	Warranty:	5 years
Rated Life:	176,000 (L70) hours		

Product Options

Mounting	Visor
Trunnion Bracket Mount Slipfitter Mount	Visor Kit

400 Watt LED Flood Light | High Lumens | 5000K | 100V-277V | Marine Grade



Product Details

SKU: MLLG-AG-LED-IMF-400-5-60-TR-MG

Web ID: 2148

400 Watt flood light - marine grade produces 56000 lumens at 140 lumens/watt. The high energy efficiency of these lights will provide significant energy savings compared to metal halide and halogen bulbs. This LED fixture is an ideal replacement for existing 1000 Watt Metal Halide when being energy efficient is a priority.

Aluminum lighting modules can be adjusted individually. All fixtures are equipped with a 1-10V dimmable driver and built-in 10KvA surge protection to enhance the durable construction of the unit. Ideal for outdoor projects such as perimeter security lighting marine vessel lighting and container shipyards/

Meets ISO 12944 C4 Marine Grade Specification

The fixtures come standard with a 100V-277V LED Driver to power the LED chips and come available in 5000K color temperature. 60 (std) 10 15 30 45 beam angle comes standard for ideal luminous flux. 10 15 30 45 40 100 beam angles are available. This fixture has several different mounting options including slip fitter or trunnion for near universal mounting options.

These fixtures are Wet location IP66 and High Impact IK08 Rated and can operate from -22 F to 113 F.

Product Specifications

Watts:	400	Dimmable:	1-10V
Lumens:	56000	Beam Angle:	60°(std), 10°, 15°, 30°, 45°
Lumens/Watt:	140	Optics:	Polycarbonate Optics and Tempered Glass Lens
Replaces:	1000 Watt Metal Halide	Frequency:	50/60 hz
Color Temp:	5000K	Housing:	ISO 12944 C4 Marine Grade
CRI:	70+	Fixture Color:	Gray
IP Rating:	IP66	Mounting:	Slip Fitter Trunnion
IK Rating:	IK08	EPA Rating:	1.89
Input Voltage:	100V-277V	Dimensions:	18.82 in X 10.63 in X 15.35 in
Surge Protection:	6kV line-line, 10kV line-earth	Weight:	24 lbs
Operating Temp:	-22°F to +113°F	Warranty:	5 years
Rated Life:	176,000 (L70) hours		

Product Options

Mounting	Visor
Trunnion Bracket Mount Slipfitter Mount	Visor Kit