



Commercial Lighting



Industrial Lighting



Sports Lighting

MLLG-AL-HB2 High Bay Product Family



**Why
contractors
choose us**



Free Lighting
Plans to ensure
customer
satisfaction



Dedicated
Lighting
Specialist for
each project



Large
inventory of
LED Lights

Table of Contents

	Page Number
- MLLG-AL-LED-HB2-100-50-120	3
- MLLG-AL-HB2-200-50-120	4
- MLLG-AL-LED-HB2-300-50-120	5
- MLLG-AL-LED-HB2-500-50-120	6
- MLLG-AL-LED-HB2-600-50-90	7
- MLLG-AL-LED-HB2-150-50-120-[V]	8

100 Watt UFO Light Fixture | 14800 Lumens | 5000K | 100V-277V



Product Details

SKU: MLLG-AL-LED-HB2-100-50-120

Web ID: 1537

100 Watt UFO LED high bay produces 14800 lumens and is extremely efficient with a 148 lumens/watt output and are equipped with 1-10V dimmable drivers. An aluminum die-cast heat sink provides excellent heat dispersion. You can choose either 100V-277V with 3500K or 5000K color temperature.

This UFO light allows you to choose the following mounts: Eye-Hook (std) or Surface. This fixture is IP69K rated for wet locations and IK08 certified and is resistant to high pressure temperature water and dust. It can operate in temperatures between -40 F to 140 F.

Options

3500K is available. Built to Order.

Product Specifications

Watts:	100	Dimmable:	1-10V
Lumens:	14800	Beam Angle:	120°
Lumens/Watt:	148	Optics:	Tempered Glass Lens
Replaces:	250 Watt Metal Halide	Frequency:	50 / 60 hz
Color Temp:	3500K 5000K	Power Factor:	.95
CRI:	80+	THD:	20% Max
IP Rating:	IP69K	Housing:	Aluminum with Epoxy Coating
IK Rating:	IK08	Fixture Color:	Black
Input Voltage:	100V-277V	Mounting:	Eye-Hook (std) Surface
Surge Protection:	6kV line-line, 6kV line-earth	Dimensions:	10.25 in X 7.5 in
Operating Temp:	-40°F to +140°F	Weight:	7.55
Rated Life:	100,000 (L70) hours	Warranty:	5 years

Product Options

Mounting

Eye Hook
Surface Mount Kit
Pendant Mount Kit

200 Watt UFO Light Fixture | 29600 Lumens | 5000K | 100V-277V



Product Details

SKU: MLLG-AL-HB2-200-50-120

Web ID: 1539

200 Watt UFO high bay produces 29600 lumens and is extremely efficient with a 148 lumens/watt output and are equipped with 1-10V dimmable drivers. Aluminum heat sink housing provides superior heat dispersion. You can choose either 100V-277V with 3500K or 5000K color temperature.

This high bay fixture comes with available mounts: Eye-Hook (std) or Surface. This high bay is IP69K Wet location certified and is resistant to high pressure temperature water and dust and can operate in temperatures between -40 F to 140 F.

Options

3500K in 100-277V is also available. Built to Order.

Product Specifications

Watts:	200	Dimmable:	1-10V
Lumens:	29600	Beam Angle:	120°
Lumens/Watt:	148	Optics:	Tempered Glass Lens
Replaces:	400 Watt Metal Halide	Frequency:	50 / 60 hz
Color Temp:	3500K 5000K	Power Factor:	.95
CRI:	80+	THD:	20% Max
IP Rating:	IP69K	Housing:	Aluminum with Epoxy Coating
IK Rating:	IK08	Fixture Color:	Black
Input Voltage:	100V-277V	Mounting:	Eye-Hook (std) Surface
Surge Protection:	6kV line-line, 6kV line-earth	Dimensions:	11.5 in X 8 in
Operating Temp:	-40°F to +140°F	Weight:	11
Rated Life:	100,000 (L70) hours	Warranty:	5 years

Product Options

Mounting

Eye Hook Mount
Surface Mount Kit
Pendant Mount Kit

300 Watt UFO Light Fixture | 45000 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-AL-LED-HB2-300-50-120

Web ID: 1828

300 Watt UFO high bay produces 45000 lumens replaces 1000 Watt Metal Halide at 150 lumens/watt output and are equipped with 1-10V dimmable drivers. Heavy duty Aluminum housing provides excellent dispersion of heat. Available in 5000K Color Temperature and 100V-277V or 277V-480V Optional.

These high bay fixtures comes with available Eye-Hook (std) or Surface mounts for simple and easy mounting. This fixture is IP69K rated for wet locations and is resistant to high-pressure water temperature water and dust and can operate in temperatures between -22 F to 140 F.

Options

High Voltage - 277-480V

Product Specifications

Watts:	300	Dimmable:	1-10V
Lumens:	45000	Beam Angle:	120°
Lumens/Watt:	150	Optics:	Tempered Glass Lens
Replaces:	1000 Watt Metal Halide	Frequency:	50 / 60 hz
Color Temp:	5000K	Power Factor:	.95
CRI:	80+	THD:	20% Max
IP Rating:	IP69K	Housing:	Aluminum with Epoxy Coating
IK Rating:	IK08	Fixture Color:	Black
Input Voltage:	100V-277V 277V-480V Optional	Mounting:	Eye-Hook (std) Surface
Surge Protection:	6kV line-line, 6kV line-earth	Dimensions:	11.5 in X 8 in
Operating Temp:	-22°F to +140°F	Weight:	11
Rated Life:	100,000 (L70) hours	Warranty:	5 years

Product Options

Mounting

Eye Hook
Surface Mount Kit
Pendant Mount Kit

500 Watt UFO Light Fixture | 75000 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-AL-LED-HB2-500-50-120

Web ID: 1953

500 Watt UFO high bay produces 75000 lumens and is extremely efficient with a 150 lumens/watt output and are equipped with 1-10V dimmable drivers. Aluminum heat sink housing provides superior heat dispersion. You can choose either 100V-277V or 277V-480V Optional with 5000K color temperature. Motion sensor kit with remote control is available for higher energy savings.

This UFO LED light comes with available mounts: Eye-Hook (std). This UFO Light Fixture is IP69K Wet location certified and is resistant to high pressure temperature water and dust and can operate in temperatures between -40 F to 140 F.

Product Specifications

Watts:	500	Dimmable:	1-10V
Lumens:	75000	Beam Angle:	120°
Lumens/Watt:	150	Optics:	Tempered Glass Lens
Replaces:	1000 Watt Metal Halide	Frequency:	50 / 60 hz
Color Temp:	5000K	Power Factor:	.95
CRI:	80+	THD:	20% Max
IP Rating:	IP69K	Housing:	Aluminum with Epoxy Coating
IK Rating:	IK08	Fixture Color:	Black
Input Voltage:	100V-277V 277V-480V Optional	Mounting:	Eye-Hook (std)
Surge Protection:	6kV line-line, 10kV line-earth	Dimensions:	14.1 in X 9.25 in
Operating Temp:	-40°F to +140°F	Weight:	21.6 lbs
Rated Life:	100,000 (L70) hours	Warranty:	5 years

600 Watt UFO Light Fixture | 98900 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-AL-LED-HB2-600-50-90

Web ID: 2139

600 Watt UFO lights produces 98900 lumens and is extremely efficient with a 165 lumens / watt output and are equipped with 0-10V dimmable drivers. Diecast aluminum heat sink housing provides superior heat dispersion. Voltage is 100V-277V with 5000K color temperature.

These LED Fixtures come with available mounts: Eye-Hook (std) or Yoke (std). This UFO Light Fixture is IP65 Wet location certified and is resistant to high pressure temperature water and dust and can operate in temperatures between -22 F to 122 F.

Product Specifications

Watts:	600	Dimmable:	0-10V
Lumens:	98900	Beam Angle:	90°
Lumens/Watt:	165	Optics:	Poly Carbonate Lens
Replaces:	2000 Watt Metal Halide	Frequency:	50 / 60 hz
Color Temp:	5000K	Power Factor:	.9
CRI:	70+	THD:	20% Max
IP Rating:	IP65	Housing:	Die-Cast Aluminium
Input Voltage:	100V-277V	Fixture Color:	Black
Surge Protection:	6kV line-line, 10kV line-earth	Mounting:	Eye-Hook (std) Yoke (std)
Operating Temp:	-22°F to +122°F	Dimensions:	14.75 in X 15.33 in
Rated Life:	100,000 (L70) hours	Weight:	32.2 lbs
		Warranty:	5 years

150 Watt UFO Light Fixture | 22200 Lumens | 5000K | 100V-277V or 277-480V



Product Details

SKU: MLLG-AL-LED-HB2-150-50-120-[V]

Web ID: 1538

150 Watt UFO LED fixtures produces 22200 lumens replacing 400 Watt Metal Halide at 148 lumens/watt output and are equipped with 1-10V dimmable drivers. The Aluminum Heat sink provides excellent heat dispersion. You can choose 100V-277V or 277V-480V with 3500K or 5000K color temperature. This fixture comes with an available Eye-Hook (std) or Surface for simple and easy mounting.

These UFO lights is IP69K rated for wet locations and IK08 impact certified. It is resistant to high pressure temperature water and dust and can operate in temperatures between -40 F to 140 F.

Options

3500K in 100-277V is also available. Built to Order.

Product Specifications

Watts:	150	Dimmable:	1-10V
Lumens:	22200	Beam Angle:	120°
Lumens/Watt:	148	Optics:	Tempered Glass Lens
Replaces:	400 Watt Metal Halide	Frequency:	50 / 60 hz
Color Temp:	3500K 5000K	Power Factor:	.95
CRI:	80+	THD:	20% Max
IP Rating:	IP69K	Housing:	Aluminum with Epoxy Coating
IK Rating:	IK08	Fixture Color:	Black
Input Voltage:	100V-277V 277V-480V	Mounting:	Eye-Hook (std) Surface
Surge Protection:	6kV line-line, 6kV line-earth	Dimensions:	10.25 in X 7.5 in
Operating Temp:	-40°F to +140°F	Weight:	7.55
Rated Life:	100,000 (L70) hours	Warranty:	5 years

Product Options

Mounting

Eye Hook
Surface Mount Kit
Pendant Mount Kit