



Commercial Lighting



Industrial Lighting



Sports Lighting

MLLG-AL-LED-DL LED Recessed Product Family



**Why
contractors
choose us**



Free Lighting
Plans to ensure
customer
satisfaction



Dedicated
Lighting
Specialist for
each project



Large
inventory of
LED Lights

Table of Contents

	Page Number
- MLLG-AL-LED-DL-4-13-CC	3
- MLLG-AL-LED-DL-6-22-CC	4
- MLLG-AL-LED-DL-8-30-CC	5
- MLLG-AL-LED-DL-10-40-CC	6

7 / 10 / 13 Wattage Adjustable 4 Inch LED Downlight | 600 to 1050 Lumens



Product Details

SKU: MLLG-AL-LED-DL-4-13-CC

Web ID: 1987

4 inch LED recessed light retrofit has a low-profile design with smooth trim. The 120 beam angle provides evenly distributed lighting. It is designed to operate on 100V-277V power supply.

You can select 2700K or 3000K or 3500K or 4000K or 5000K color temperature by switching a toggle switch. 0-10V dimmable driver included. Power can also be set. Choose 7 | 10 | 13 Watts by setting a toggle switch.

Install using included TP24 or E26 connector. Spring clips make installation easy.

Product Specifications

Watts:	7 10 13	Dimmable:	0-10V
Lumens:	600 850 1950	Beam Angle:	120°
Lumens/Watt:	86	Base:	E26
Replaces:	50 Watt Metal Halide	Power Factor:	.95
Color Temp:	2700K 3000K 3500K 4000K 5000K	Housing:	Aluminum with Polycarbonate Lens
CRI:	90+	Fixture Color:	White
Input Voltage:	100V-277V	Mounting:	Recessed
Surge Protection:	2.5 kV	Dimensions:	5 3/8 in D x 3 1/16 in H
Operating Temp:	-13°F to +113°F	Weight:	1 lb
Rated Life:	50,000 (L70) hours	Warranty:	5 years

10 / 15 / 22 Watt Adjustable 6 Inch LED Downlight | 900 to 1850 Lumens



Product Details

SKU: MLLG-AL-LED-DL-6-22-CC

Web ID: 1575

6 inch LED recessed light retrofit has a low-profile design with smooth trim. The 120 beam angle provides evenly distributed lighting. It is designed to operate on 100V-277V power supply.

You can select 2700K or 3000K or 3500K or 4000K or 5000K color temperature by switching a toggle switch. 0-10V dimmable driver included. Power can also be set. Choose 10 | 15 | 22 Watts by setting a toggle switch.

Install using included TP24 or E26 connector. Spring clips make installation easy.

Product Specifications

Watts:	10 15 22	Dimmable:	0-10V
Lumens:	900 1300 1850	Beam Angle:	120°
Lumens/Watt:	90	Base:	E26
Replaces:	50 70 Watt Metal Halide	Power Factor:	.95
Color Temp:	2700K 3000K 3500K 4000K 5000K	Housing:	Aluminum with Polycarbonate Lens
CRI:	90+	Fixture Color:	White
Input Voltage:	100V-277V	Mounting:	Recessed
Surge Protection:	2.5 kV	Dimensions:	8 1/4 in D x 4 in H
Operating Temp:	-13°F to +113°F	Weight:	1.21
Rated Life:	50,000 (L70) hours	Warranty:	5 years

12 / 20 / 30 Watt Adjustable 8 Inch LED Downlight | 900 to 1850 Lumens



Product Details

SKU: MLLG-AL-LED-DL-8-30-CC

Web ID: 1576

8 inch LED recessed light retrofit has a low-profile design with smooth trim. The 120 beam angle provides evenly distributed lighting. It is designed to operate on 100V-277V power supply.

You can select 2700K or 3000K or 3500K or 4000K or 5000K color temperature by switching a toggle switch. 0-10V dimmable driver included. Power can also be set. Choose 12 | 20 | 30 Watts by setting a toggle switch.

Install using included TP24 or E26 connector. Spring clips make installation easy.

Product Specifications

Watts:	12 20 30	Dimmable:	0-10V
Lumens:	1050 1700 2400	Beam Angle:	120°
Lumens/Watt:	88	Base:	E26
Replaces:	70 100 Watt Metal Halide	Power Factor:	.95
Color Temp:	2700K 3000K 3500K 4000K 5000K	Housing:	Aluminum with Polycarbonate Lens
CRI:	90+	Fixture Color:	White
Input Voltage:	100V-277V	Mounting:	Recessed
Surge Protection:	2.5 kV	Dimensions:	10 1/4 in D x 4 7/16 in H
Operating Temp:	-13°F to +113°F	Weight:	1.5
Rated Life:	50,000 (L70) hours	Warranty:	5 years

20 / 30 / 40 Watt Adjustable 10 Inch LED Downlight | 1800 to 3000 Lumens



Product Details

SKU: MLLG-AL-LED-DL-10-40-CC

Web ID: 1913

10-inch LED recessed light retrofit has a low-profile design with smooth trim. The 120° beam angle provides evenly distributed lighting. It is designed to operate on 100V-277V power supply.

You can select 2700K or 3000K or 3500K or 4000K or 5000K color temperature by switching a toggle switch. 0-10V dimmable driver included. Power can also be set. Choose 20 | 30 | 40 Watts by setting a toggle switch.

Install using included TP24 or E26 connector. Spring clips make installation easy.

Product Specifications

Watts:	20 30 40	Dimmable:	0-10V
Lumens:	1800 2400 3000	Beam Angle:	120°
Lumens/Watt:	88	Base:	E26
Replaces:	100 125 Watt Metal Halide	Power Factor:	.95
Color Temp:	2700K 3000K 3500K 4000K 5000K	Housing:	Aluminum with Polycarbonate Lens
CRI:	90+	Fixture Color:	White
Input Voltage:	100V-277V	Mounting:	Recessed
Surge Protection:	2.5 kV	Dimensions:	11 5/16 in D x 4 15/16 in H
Operating Temp:	-13°F to +113°F	Weight:	1.5
Rated Life:	50,000 (L70) hours	Warranty:	5 years