

Commercial Lighting

Industrial Lighting

Sports Lighting

MLLG-AL-LED-HBLIN5 High Bay Product Family





Why contractors choose us

Free Lighting
Plans to ensure
customer
satisfaction

Dedicated Lighting Specialist for each project Large inventory of LED Lights

Table of Contents

	Page Number
- MLLG-AL-LED-HBLIN5-220-50	3
- MLLG-AL-LED-HBLIN5-500-50	4



220w LED High Bay | 30580 Lumens | 5000K | 100V-277V | 2 Foot



Product Details

SKU: MLLG-AL-LED-HBLIN5-220-50

Web ID: 1847

2 Foot 220 Watt LED Linear high bay produces 30580 Lumens at 139 lumens/watt replacing 400 Watt Metal Halide. It has durable white aluminum housing and energy-efficient LED drivers to ensure high-performance lighting. The frosted Poly-Carbonate lenses are durable and impact-resistant. The housing is designed to dissipate heat.

This high bay comes with a 1-10V dimmable 100V-277V or 277V-480V LED driver. Available color temperatures are: 5000K. This fixture can be suspended using the following mounting options: Chain-Cable (std) or Pendant or Surface. Its damp location rated and operates in temperatures ranging from -22 F to 122 F.

Product Specifications

Watts:	220	Dimmable:	1-10V
Lumens:	30580	Beam Angle:	120°
Lumens/Watt:	139	Frequency:	50 / 60 hz
Replaces:	400 Watt Metal Halide	Power Factor:	.90
Color Temp:	5000K	THD:	20% Max
CRI:	80+	Housing:	Aluminum
Input Voltage:	100V-277V 277V-480V	Fixture Color:	White
Surge Protection:	4kV line-line, 6kV line-earth	Mounting:	Chain-Cable (std) Pendant Surface
Operating Temp:	-22°F to +122°F	Dimensions:	24 1/2 in X 11 7/8 in X 1 7/8 in
Rated Life:	200,000 (L70) hours	Weight:	8.5 lbs
		Warranty:	5 years

Product Options

Mount	Wire Guard
Wire Mount Pendant Mount Surface Mount	Wire Guard Kit



500 Watt Linear High Bay Fixture | 68000 Lumens | 5000K | 100V-277V



Product Details

SKU: MLLG-AL-LED-HBLIN5-500-50

Web ID: 1706

High Power 4 foot 500 Watt Linear LED fixtures produces 68000 lumens at 136 lumens/watt replacing 1000 Watt Metal Halide. It has durable white aluminum housing and energy-efficient LED drivers to ensure high-performance lighting. The frosted Poly-Carbonate lenses are durable and impact-resistant. The housing is designed to dissipate heat.

These high bays comes with a 1-10V dimmable 100V-277V LED driver. Available color temperatures are: 5000K. This high bay fixture can be suspended using the following mounting options: Chain-Cable (std) or Pendant or Surface. Its damp location rated and operates in temperatures ranging from -22 F to 122 F.

Product Specifications

Watts:	500	Dimmable:	1-10V
Lumens:	68000	Beam Angle:	120°
Lumens/Watt:	136	Frequency:	50 / 60 hz
Replaces:	1000 Watt Metal Halide	Power Factor:	.90
Color Temp:	5000K	THD:	20% Max
CRI:	80+	Housing:	Aluminum
Input Voltage:	100V-277V	Fixture Color:	White
Operating Temp:	-22°F to +122°F	Mounting:	Chain-Cable (std) Pendant Surface
Rated Life:	100,000 (L70) hours	Dimensions:	39.5 in L X 12 in W X 2.2 in H
		Weight:	14.6
		Warranty:	5 years

Product Options

Mount	
Wire Mount	
Pendant Mount	
Surface Mount	