



Commercial Lighting



Industrial Lighting



Sports Lighting

MLLG-AL-LED-HMSL Stadium Light Product Family



**Why
contractors
choose us**



Free Lighting
Plans to ensure
customer
satisfaction



Dedicated
Lighting
Specialist for
each project



Large
inventory of
LED Lights

Table of Contents

	Page Number
- MLLG-AL-LED-HMSL-500-5-45	3
- MLLG-AL-LED-HMSL-500-5-45-HV	4
- MLLG-AL-LED-HMSL-750-5-45	5

500w LED Stadium Light | 74000 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-AL-LED-HMSL-500-5-45

Web ID: 2018

500 Watt stadium light replaces 1000 Watt Metal Halide and is energy efficient at 148 lumens / Watt output producing 74000 lumens. It is equipped with a 1-10V dimmable LED driver. Die-cast aluminum housing with a protective coating provides excellent heat dissipation. Available in 100V-277V Voltage and 5000K color temperature.

This fixture includes a trunnion mount for outdoor installation. This fixture is Wet location rated IP66 rated. These LED sports lights can operate in temperatures between -40 F to 122 F. 10kV Surge Protection included. Comes with a 6.5 foot Power Cord. This fixture is equipped with a 45 optic.

Customer Installed Options

Slip fitter Mount

30 degree optic

Product Specifications

Watts:	500	Dimmable:	1-10V
Lumens:	74000	Beam Angle:	45°
Lumens/Watt:	148	Frequency:	50 / 60 hz
Replaces:	1000 Watt Metal Halide	Power Factor:	.90
Color Temp:	5000K	THD:	20% Max
CRI:	70+	Mounting:	Trunnion
IP Rating:	IP66	EPA Rating:	1.37
Input Voltage:	100V-277V	Dimensions:	15.5 in D X 14.5 in
Operating Temp:	-40°F to +122°F	Weight:	31
Rated Life:	50,000 (L70) hours	Warranty:	5 years

Product Options

Slipfitter Mount

No Slipfitter
Slipfitter

Optics

45 degrees (std)
30 degrees (opt)

500 Watt LED Stadium Light | 71700 Lumens | 5000K | 277-480V



Product Details

SKU: MLLG-AL-LED-HMSL-500-5-45-HV

Web ID: 2016

500 Watt Sports / Area Light replaces 1000 Watt Metal Halide and is energy efficient at 143 lumens / Watt output producing 71700 lumens. It is equipped with a 1-10V dimmable LED driver. Die-cast aluminum housing with protective coating provides excellent heat dissipation. Available in 277V-480V Voltage and 5000K color temperature.

This fixture includes a trunnion mount for outdoor installation. This fixture is Wet location rated IP66 rated. These LED sport lights can operate in temperatures between -40 F to 122 F. 10kV Surge Protection included. Comes with a 6.5 foot Power Cord. This fixture is equipped with a 45 optic.

Customer Installed Options

Slip fitter Mount

30 degree optic

Product Specifications

Watts:	500	Dimmable:	1-10V
Lumens:	71700	Beam Angle:	45°
Lumens/Watt:	143	Frequency:	50 / 60 hz
Replaces:	1000 Watt Metal Halide	Power Factor:	.90
Color Temp:	5000K	THD:	20% Max
CRI:	70+	Mounting:	Trunnion
IP Rating:	IP66	EPA Rating:	1.37
Input Voltage:	277V-480V	Dimensions:	15.5 in D X 14.5 in
Operating Temp:	-40°F to +122°F	Weight:	31
Rated Life:	50,000 (L70) hours	Warranty:	5 years

Product Options

Slipfitter Mount

No Slipfitter
Slipfitter

Optics

45 degrees (std)
30 degrees (opt)

750 Watt LED Stadium Light | 93200 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-AL-LED-HMSL-750-5-45

Web ID: 2017

750 Watt Sport / Area Light replaces 1500 Watt Metal Halide and is energy efficient at 124 lumens / Watt output producing 93200 lumens. It is equipped with a 1-10V dimmable LED driver. Die-cast aluminum housing with a protective coating provides excellent heat dissipation. Available in 100V-277V Voltage and 5000K color temperature.

This fixture includes a trunnion mount for outdoor installation. This fixture is Wet location rated IP66 rated. These LED sport lights can operate in temperatures between -40 F to 122 F. 10kV Surge Protection included. Comes with a 6.5 foot Power Cord. This fixture is equipped with a 45 optic.

Customer Installed Options

Slip fitter Mount

30 degree optic

Product Specifications

Watts:	750	Dimmable:	1-10V
Lumens:	93200	Beam Angle:	45°
Lumens/Watt:	124	Frequency:	50 / 60 hz
Replaces:	1500 Watt Metal Halide	Power Factor:	.90
Color Temp:	5000K	THD:	20% Max
CRI:	70+	Mounting:	Trunnion
IP Rating:	IP66	EPA Rating:	1.37
Input Voltage:	100V-277V	Dimensions:	19.75 in D X 18.5 in
Operating Temp:	-40°F to +122°F	Weight:	56
Rated Life:	50,000 (L70) hours	Warranty:	5 years

Product Options

Slipfitter Mount

No Slipfitter
Slipfitter