



Commercial Lighting



Industrial Lighting



Sports Lighting

## MLLG-AL-LED-WPFL Wall Pack Product Family



**Why  
contractors  
choose us**



Free Lighting  
Plans to ensure  
customer  
satisfaction



Dedicated  
Lighting  
Specialist for  
each project



Large  
inventory of  
LED Lights

# Table of Contents

	Page Number
- MLLG-AL-LED-WPFL-30-CC	3
- MLLG-AL-LED-WPFL-50-CC	4
- MLLG-AL-LED-WPFL-50-CC-EMB	5
- MLLG-AL-LED-WPFL-80-CC	6
- MLLG-AL-LED-WPFL-80-CC-EMB	7
- MLLG-AL-LED-WPFL-120-CC	8

**30w LED Wall Pack | 4834 Lumens | Color Changeable | 100-277V | Forward Throw**



**Product Details**

**SKU:** MLLG-AL-LED-WPFL-30-CC

**Web ID:** 2040

30 Watt flood wall pack produces 4834 lumens at 161 lumens/watt replacing 150 Watt Metal Halide. It has a heavy-duty die-cast aluminum housing and tempered glass lens. This fixture is designed for outdoor locations. Excellent impact corrosion and UV resistance with the dark bronze polyester powder finish. Available in 100V-277V.

This fixture allows you to change the color temperature by flipping a switch: 3000K or 4000K or 5000K Color Temperature. The fixture is bronze in color. The housing has a removable hinge door and multiple points of entry - making installation quick and easy. 1/2 in threaded conduit entry with coin plug. They are IP65 UL 1598 wet location rated.

**Product Specifications**

<b>Watts:</b>	30	<b>Dimmable:</b>	1-10V
<b>Lumens:</b>	4834	<b>Beam Angle:</b>	120°
<b>Lumens/Watt:</b>	161	<b>Frequency:</b>	50-60Hz
<b>Replaces:</b>	150 Watt Metal Halide	<b>Power Factor:</b>	> .90
<b>Color Temp:</b>	3000K   4000K   5000K	<b>THD:</b>	< 20%
<b>CRI:</b>	70+	<b>Housing:</b>	Powder Coated Die-Cast Aluminum with Polycarbonate Lens
<b>IP Rating:</b>	IP65	<b>Fixture Color:</b>	Bronze
<b>Input Voltage:</b>	100V-277V	<b>Mounting:</b>	Wall
<b>Operating Temp:</b>	-40°F to +122°F	<b>Dimensions:</b>	10.25 in L X 9.5 in W X 7.5 in H
<b>Rated Life:</b>	50,000 (L70) hours	<b>Weight:</b>	5.3
		<b>Warranty:</b>	5 years

**Product Options**

**Photocell**

Photocell

## 50 Watt LED Wall Pack | 7719 Lumens | Color Changeable | 100-277V



### Product Details

**SKU:** MLLG-AL-LED-WPFL-50-CC

**Web ID:** 1864

50 Watt flood wall pack produces 7719 lumens at 154 lumens/watt replacing 150 Watt Metal Halide. It has a heavy-duty die-cast aluminum housing and tempered glass lens. This fixture is designed for outdoor locations. Excellent impact corrosion and UV resistance with the dark bronze polyester powder finish. Available in 100V-277V.

This fixture allows you to change the color temperature by flipping a switch: 3000K or 4000K or 5000K Color Temperature. The fixture is bronze in color. The housing has a removable hinge door and multiple points of entry - making installation quick and easy. 1/2 in threaded conduit entry with coin plug. They are IP65 UL 1598 wet location rated.

### Product Specifications

<b>Watts:</b>	50	<b>Dimmable:</b>	1-10V
<b>Lumens:</b>	7719	<b>Beam Angle:</b>	120°
<b>Lumens/Watt:</b>	154	<b>Frequency:</b>	50-60Hz
<b>Replaces:</b>	150 Watt Metal Halide	<b>Power Factor:</b>	> .90
<b>Color Temp:</b>	3000K   4000K   5000K	<b>THD:</b>	< 20%
<b>CRI:</b>	70+	<b>Housing:</b>	Powder Coated Die-Cast Aluminum with Polycarbonate Lens
<b>IP Rating:</b>	IP65	<b>Fixture Color:</b>	Bronze
<b>Input Voltage:</b>	100V-277V	<b>Mounting:</b>	Wall
<b>Operating Temp:</b>	-40°F to +122°F	<b>Dimensions:</b>	10.4 in L X 9.5 in W X 7.5 in H
<b>Rated Life:</b>	50,000 (L70) hours	<b>Weight:</b>	7.9
		<b>Warranty:</b>	5 years

### Product Options

**Photocell**

Photocell

## 50 Watt LED Forward Throw Wall Pack | 7719 Lumens



### Product Details

**SKU:** MLLG-AL-LED-WPFL-50-CC-EMB

**Web ID:** 1865

50 Watt flood wall pack produces 7719 lumens at 154 lumens/watt replacing 150 Watt Metal Halide. It has a heavy-duty die-cast aluminum housing and tempered glass lens. This fixture is designed for outdoor locations. Excellent impact corrosion and UV resistance with the dark bronze polyester powder finish. Available in 100V-277V.

This fixture allows you to change the color temperature by flipping a switch: 3000K or 3000K or 4000K or 5000K Color Temperature. The fixture is bronze in color.

This fixture comes standard with a backup battery for emergencies.

The housing has a removable hinge door and multiple points of entry - making installation quick and easy. 1/2 in threaded conduit entry with coin plug. They are IP65 UL 1598 wet location rated.

### Product Specifications

<b>Watts:</b>	50	<b>Dimmable:</b>	1-10V
<b>Lumens:</b>	7719	<b>Beam Angle:</b>	120°
<b>Lumens/Watt:</b>	154	<b>Frequency:</b>	50-60Hz
<b>Replaces:</b>	150 Watt Metal Halide	<b>Power Factor:</b>	> .90
<b>Color Temp:</b>	3000K   3000K   4000K   5000K	<b>THD:</b>	< 20%
<b>CRI:</b>	70+	<b>Housing:</b>	Powder Coated Die-Cast Aluminum with Polycarbonate Lens
<b>IP Rating:</b>	IP65	<b>Fixture Color:</b>	Bronze
<b>Input Voltage:</b>	100V-277V	<b>Mounting:</b>	Wall
<b>Operating Temp:</b>	-40°F to +122°F	<b>Dimensions:</b>	10.4 in L X 9.5 in W X 7.5 in H
<b>Rated Life:</b>	50,000 (L70) hours	<b>Weight:</b>	7.9
		<b>Warranty:</b>	5 years

## 80 Watt LED Forward Throw Wall Pack | 12174 Lumens



### Product Details

**SKU:** MLLG-AL-LED-WPFL-80-CC

**Web ID:** 1866

80 Watt flood wall pack produces 12174 lumens at 152 lumens/watt replacing 250 Watt Metal Halide. It has a heavy-duty die-cast aluminum housing and tempered glass lens. This fixture is designed for outdoor locations. Excellent impact corrosion and UV resistance with the dark bronze polyester powder finish. Available in 100V-277V.

This fixture allows you to change the color temperature by flipping a switch: 3000K or 4000K or 5000K Color Temperature. The fixture is bronze in color. The housing has a removable hinge door and multiple points of entry - making installation quick and easy. 1/2 in threaded conduit entry with coin plug. They are IP65 UL 1598 wet location rated.

### Product Specifications

<b>Watts:</b>	80	<b>Dimmable:</b>	1-10V
<b>Lumens:</b>	12174	<b>Beam Angle:</b>	120°
<b>Lumens/Watt:</b>	152	<b>Frequency:</b>	50-60Hz
<b>Replaces:</b>	250 Watt Metal Halide	<b>Power Factor:</b>	> .90
<b>Color Temp:</b>	3000K   4000K   5000K	<b>THD:</b>	< 20%
<b>CRI:</b>	70+	<b>Housing:</b>	Powder Coated Die-Cast Aluminum with Polycarbonate Lens
<b>IP Rating:</b>	IP65	<b>Fixture Color:</b>	Bronze
<b>Input Voltage:</b>	100V-277V	<b>Mounting:</b>	Wall
<b>Operating Temp:</b>	-40°F to +122°F	<b>Dimensions:</b>	14.2 in L X 9.5 in W X 7.6 in H
<b>Rated Life:</b>	50,000 (L70) hours	<b>Weight:</b>	7.9
		<b>Warranty:</b>	5 years

### Product Options

#### Motion Sensor

Motion Sensor  
Photocell



## 80 Watt LED Forward Throw Wall Pack | 12174 Lumens



### Product Details

**SKU:** MLLG-AL-LED-WPFL-80-CC-EMB

**Web ID:** 1867

80 Watt flood wall pack produces 12174 lumens at 152 lumens/watt replacing 250 | 250 Watt Metal Halide. It has a heavy-duty die-cast aluminum housing and tempered glass lens. This fixture is designed for outdoor locations. Excellent impact corrosion and UV resistance with the dark bronze polyester powder finish. Available in 100V-277V.

This fixture allows you to change the color temperature by flipping a switch: 3000K or 4000K or 5000K Color Temperature. The fixture is bronze in color. The housing has a removable hinge door and multiple points of entry - making installation quick and easy. 1/2 in threaded conduit entry with coin plug. They are IP65 UL 1598 wet location rated and are perfect for retrofitting and new construction applications.

This fixture comes with an Emergency Backup Battery.

### Product Specifications

<b>Watts:</b>	80	<b>Dimmable:</b>	1-10V
<b>Lumens:</b>	12174	<b>Beam Angle:</b>	120°
<b>Lumens/Watt:</b>	152	<b>Frequency:</b>	50-60Hz
<b>Replaces:</b>	250   250 Watt Metal Halide	<b>Power Factor:</b>	> .90
<b>Color Temp:</b>	3000K   4000K   5000K	<b>THD:</b>	< 20%
<b>CRI:</b>	70+	<b>Housing:</b>	Powder Coated Die-Cast Aluminum with Polycarbonate Lens
<b>IP Rating:</b>	IP65	<b>Fixture Color:</b>	Bronze
<b>Input Voltage:</b>	100V-277V	<b>Mounting:</b>	Wall
<b>Operating Temp:</b>	-40°F to +122°F	<b>Dimensions:</b>	14.2 in L X 9.5 in W X 7.6 in H
<b>Rated Life:</b>	50,000 (L70) hours	<b>Weight:</b>	7.9
		<b>Warranty:</b>	5 years

## 120 Watt LED Forward Throw Wall Pack | 17793 Lumens



### Product Details

**SKU:** MLLG-AL-LED-WPFL-120-CC

**Web ID:** 1868

120 Watt flood wall pack produces 17793 lumens at 148 lumens/watt replacing 400 Watt Metal Halide. It has a heavy-duty die-cast aluminum housing and tempered glass lens. This fixture is designed for outdoor locations. Excellent impact corrosion and UV resistance with the dark bronze polyester powder finish. Available in 100V-277V.

This fixture allows you to change the color temperature by flipping a switch: 3000K or 4000K or 5000K Color Temperature. The fixture is bronze in color. The housing has a removable hinge door and multiple points of entry - making installation quick and easy. 1/2 in threaded conduit entry with coin plug. They are IP65 UL 1598 wet location rated.

### Product Specifications

<b>Watts:</b>	120	<b>Dimmable:</b>	1-10V
<b>Lumens:</b>	17793	<b>Beam Angle:</b>	120°
<b>Lumens/Watt:</b>	148	<b>Frequency:</b>	50-60Hz
<b>Replaces:</b>	400 Watt Metal Halide	<b>Power Factor:</b>	> .90
<b>Color Temp:</b>	3000K   4000K   5000K	<b>THD:</b>	< 20%
<b>CRI:</b>	70+	<b>Housing:</b>	Powder Coated Die-Cast Aluminum with Polycarbonate Lens
<b>IP Rating:</b>	IP65	<b>Fixture Color:</b>	Bronze
<b>Input Voltage:</b>	100V-277V	<b>Mounting:</b>	Wall
<b>Operating Temp:</b>	-40°F to +122°F	<b>Dimensions:</b>	14.2 in L X 9.5 in W X 7.6 in H
<b>Rated Life:</b>	50,000 (L70) hours	<b>Weight:</b>	9.3
		<b>Warranty:</b>	5 years

### Product Options

**Motion Sensor**

Motion Sensor