



Commercial Lighting



Industrial Lighting



Sports Lighting

## MLLG-AL-LED-WPS Wall Pack Product Family



**Why  
contractors  
choose us**



Free Lighting  
Plans to ensure  
customer  
satisfaction



Dedicated  
Lighting  
Specialist for  
each project



Large  
inventory of  
LED Lights

# Table of Contents

|                                | Page Number |
|--------------------------------|-------------|
| - MLLG-LN-LED-WPS-12-50-PC-EMB | 3           |
| - MLLG-AL-LED-WPS-13-CC-PC     | 4           |
| - MLLG-AL-LED-WPS-18-CC-PC     | 5           |
| - MLLG-AL-LED-WPS-26-CC-PC     | 6           |

## 12 Watt LED Wall Pack With Photocell | 960 Lumens | 5000K



### Product Details

**SKU:** MLLG-LN-LED-WPS-12-50-PC-EMB

**Web ID:** 2080

12 Watt wall pack produces 960 lumens at 80 lumens/watt and is a commercial-grade outdoor fixture. These wall packs are available in color temperature: 5000K. The die-cast aluminum housing provides excellent heat dissipation. Its impact-resistant polycarbonate lens shields the fixture and helps to prevent glare.

Years of trouble-free operation with durable die-cast housing and anti-static powder-coated paint. Proper dusk-to-dawn operation with the built-in photocell. Standard Voltage is 100V-277V. They are IP65 Wet Location Rated and will stand up to many years of punishing weather.

This wall pack comes with a built-in emergency backup battery. 4-watt Emergency backup for 90 minutes at 433 lumens. Comes with a 4.8V 1800mAh Nickel Cadmium Battery that powers the light when needed.

### Product Specifications

|                        |                      |                       |   |
|------------------------|----------------------|-----------------------|---|
| <b>Watts:</b>          | 12                   | <b>Dimmable:</b>      | No  |
| <b>Lumens:</b>         | 960                  | <b>Beam Angle:</b>    | Type 5  |
| <b>Lumens/Watt:</b>    | 80                   | <b>Frequency:</b>     | 50-60Hz   |
| <b>Replaces:</b>       | 70 Watt Metal Halide | <b>Power Factor:</b>  | > .90   |
| <b>Color Temp:</b>     | 5000K                | <b>THD:</b>           | < 20%   |
| <b>CRI:</b>            | 70+                  | <b>Housing:</b>       | Powder Coated Die-Cast Aluminum with Polycarbonate Lens |
| <b>IP Rating:</b>      | IP65                 | <b>Fixture Color:</b> | Bronze  |
| <b>Input Voltage:</b>  | 100V-277V            | <b>Mounting:</b>      | Wall  |
| <b>Operating Temp:</b> | 14°F to +104°F       | <b>Dimensions:</b>    | 10.4 in H X 6.3 in W X 3.86 in D                        |
| <b>Rated Life:</b>     | 50,000 (L70) hours   | <b>Weight:</b>        | 1.4   |
|                        |                      | <b>Warranty:</b>      | 5 years   |

## 13 Watt LED Wall Pack With Photocell | 1622 Lumens



### Product Details

**SKU:** MLLG-AL-LED-WPS-13-CC-PC

**Web ID:** 1450

13 Watt wall pack produces 1622 lumens at 125 lumens/watt and is a commercial-grade outdoor fixture. These wall packs allow you to select the color you want: 3000K or 4000K or 5000K. The die-cast aluminum housing provides excellent heat dissipation. Its impact-resistant polycarbonate lens shields the fixture and helps to prevent glare.

Years of trouble-free operation with durable die-cast housing and anti-static powder-coated paint. Proper dusk-to-dawn operation with the built-in photocell. Standard Voltage is 100V-277V. They are IP65 Wet Location Rated and will stand up to many years of punishing weather.

### Product Specifications

|                        |                       |                       |   |
|------------------------|-----------------------|-----------------------|---|
| <b>Watts:</b>          | 13                    | <b>Dimmable:</b>      | No  |
| <b>Lumens:</b>         | 1622                  | <b>Beam Angle:</b>    | Type 5  |
| <b>Lumens/Watt:</b>    | 125                   | <b>Frequency:</b>     | 50-60Hz   |
| <b>Replaces:</b>       | 70 Watt Metal Halide  | <b>Power Factor:</b>  | > .90   |
| <b>Color Temp:</b>     | 3000K   4000K   5000K | <b>THD:</b>           | < 20%   |
| <b>CRI:</b>            | 70+                   | <b>Housing:</b>       | Powder Coated Die-Cast Aluminum with Polycarbonate Lens |
| <b>IP Rating:</b>      | IP65                  | <b>Fixture Color:</b> | Black   |
| <b>Input Voltage:</b>  | 100V-277V             | <b>Mounting:</b>      | Wall  |
| <b>Operating Temp:</b> | -31°F to +104°F       | <b>Dimensions:</b>    | 8 in H X 5.5 in W X 3 in D                              |
| <b>Rated Life:</b>     | 50,000 (L70) hours    | <b>Weight:</b>        | 1.4   |
|                        |                       | <b>Warranty:</b>      | 5 years   |

## 18 Watt LED Wall Pack With Photocell | 2187 Lumens



### Product Details

**SKU:** MLLG-AL-LED-WPS-18-CC-PC

**Web ID:** 1841

18 Watt wall pack produces 2187 lumens at 122 lumens/watt and is a commercial-grade outdoor fixture. These wall packs allow you to select the color you want: 3000K or 4000K or 5000K. The die-cast aluminum housing provides excellent heat dissipation. Its impact-resistant polycarbonate lens shields the fixture and helps to prevent glare.

Years of trouble-free operation with durable die-cast housing and anti-static powder-coated paint. Proper dusk-to-dawn operation with the built-in photocell. Standard Voltage is 100V-277V. They are IP65 Wet Location Rated and will stand up to many years of punishing weather.

### Product Specifications

|                        |                       |                       |   |
|------------------------|-----------------------|-----------------------|---|
| <b>Watts:</b>          | 18                    | <b>Dimmable:</b>      | No  |
| <b>Lumens:</b>         | 2187                  | <b>Beam Angle:</b>    | Type 5  |
| <b>Lumens/Watt:</b>    | 122                   | <b>Frequency:</b>     | 50-60Hz   |
| <b>Replaces:</b>       | 100 Watt Metal Halide | <b>Power Factor:</b>  | > .90   |
| <b>Color Temp:</b>     | 3000K   4000K   5000K | <b>THD:</b>           | < 20%   |
| <b>CRI:</b>            | 70+                   | <b>Housing:</b>       | Powder Coated Die-Cast Aluminum with Polycarbonate Lens |
| <b>IP Rating:</b>      | IP65                  | <b>Fixture Color:</b> | Black   |
| <b>Input Voltage:</b>  | 100V-277V             | <b>Mounting:</b>      | Wall  |
| <b>Operating Temp:</b> | -31°F to +104°F       | <b>Dimensions:</b>    | 8 in H X 5.5 in W X 3 in D                              |
| <b>Rated Life:</b>     | 50,000 (L70) hours    | <b>Weight:</b>        | 1.4   |
|                        |                       | <b>Warranty:</b>      | 5 years   |

## 26 Watt LED Wall Pack With Photocell | 3385 Lumens



### Product Details

**SKU:** MLLG-AL-LED-WPS-26-CC-PC

**Web ID:** 1842

26 Watt wall pack produces 3385 lumens at 130 lumens/watt and is a commercial-grade outdoor fixture. These wall packs allow you to select the color you want: 3000K or 4000K or 5000K. The die-cast aluminum housing provides excellent heat dissipation. Its impact-resistant polycarbonate lens shields the fixture and helps to prevent glare.

Years of trouble-free operation with durable die-cast housing and anti-static powder-coated paint. Proper dusk-to-dawn operation with the built-in photocell. Standard Voltage is 100V-277V. They are IP65 Wet Location Rated and will stand up to many years of punishing weather.

### Product Specifications

|                        |                       |                       |   |
|------------------------|-----------------------|-----------------------|---|
| <b>Watts:</b>          | 26                    | <b>Dimmable:</b>      | No  |
| <b>Lumens:</b>         | 3385                  | <b>Beam Angle:</b>    | Type 5  |
| <b>Lumens/Watt:</b>    | 130                   | <b>Frequency:</b>     | 50-60Hz   |
| <b>Replaces:</b>       | 100 Watt Metal Halide | <b>Power Factor:</b>  | > .90   |
| <b>Color Temp:</b>     | 3000K   4000K   5000K | <b>THD:</b>           | < 20%   |
| <b>CRI:</b>            | 70+                   | <b>Housing:</b>       | Powder Coated Die-Cast Aluminum with Polycarbonate Lens |
| <b>IP Rating:</b>      | IP65                  | <b>Fixture Color:</b> | Black   |
| <b>Input Voltage:</b>  | 100V-277V             | <b>Mounting:</b>      | Wall  |
| <b>Operating Temp:</b> | -31°F to +104°F       | <b>Dimensions:</b>    | 8 in W X 5.5 in H X 3 in D                              |
| <b>Rated Life:</b>     | 50,000 (L70) hours    | <b>Weight:</b>        | 1.4   |
|                        |                       | <b>Warranty:</b>      | 5 years   |