



Commercial Lighting



Industrial Lighting



Sports Lighting

## MLLG-GI-LED-FLD3 Flood Light Product Family



**Why  
contractors  
choose us**



Free Lighting  
Plans to ensure  
customer  
satisfaction



Dedicated  
Lighting  
Specialist for  
each project



Large  
inventory of  
LED Lights

# Table of Contents

	Page Number
- MLLG-GI-LED-FLD3-50	3
- MLLG-GI-LED-FLD3-120	4

## 50 Watt LED Flood Light | 6900 Lumens | 5000K | 100-277V



### Product Details

**SKU:** MLLG-GI-LED-FLD3-50

**Web ID:** 1412

50 Watt flood light produces 6900 lumens at 138 lumens/watt replacing 175 Watt Metal Halide. Die-cast aluminum fixture/heatsink is bronze powder coated for years of maintenance-free life. Flood Light can be equipped with a 1-10V | Optional dimmable driver.

It comes with a 100V-277V LED Driver and you can choose between 5000K color temperature. The standard beam angle is 120°. This fixture is supplied with a Trunnion mount. It is IP65 rated for wet locations and can operate in temperatures ranging from -31 F to 131 F.

### Product Specifications

<b>Watts:</b>	50	<b>Dimmable:</b>	1-10V   Optional
<b>Lumens:</b>	6900	<b>Beam Angle:</b>	120°
<b>Lumens/Watt:</b>	138	<b>Optics:</b>	Polycarbonate Lens
<b>Replaces:</b>	175 Watt Metal Halide	<b>Frequency:</b>	50/60 hz
<b>Color Temp:</b>	5000K	<b>THD:</b>	< 15%
<b>CRI:</b>	75+	<b>Housing:</b>	Aluminum
<b>IP Rating:</b>	IP65	<b>Fixture Color:</b>	Bronze
<b>Input Voltage:</b>	100V-277V	<b>Mounting:</b>	Trunnion
<b>Operating Temp:</b>	-31°F to +131°F	<b>Dimensions:</b>	11.5 in X 7 in X 5.5 in
<b>Rated Life:</b>	50,000 hours	<b>Weight:</b>	14 lbs
		<b>Warranty:</b>	6 years

## 120 Watt LED Flood Light | 15080 Lumens | 5000K | 100-277V



### Product Details

**SKU:** MLLG-GI-LED-FLD3-120

**Web ID:** 1413

120 Watt flood light produces 15080 lumens at 126 lumens/watt replacing 400 Watt Metal Halide. Die-cast aluminum fixture/heatsink is bronze powder coated for years of maintenance-free life. Flood Light can be equipped with a No dimmable driver.

It comes with a 100V-277V or 347V-480V LED Driver and you can choose between 4000K or 5000K color temperature. The standard beam angle is 120°. This fixture is supplied with a Arm or Slip Fitter or Trunnion mount. It is IP65 rated for wet locations and can operate in temperatures ranging from -31 F to 131 F.

### Product Specifications

<b>Watts:</b>	120	<b>Dimmable:</b>	No
<b>Lumens:</b>	15080	<b>Beam Angle:</b>	120°
<b>Lumens/Watt:</b>	126	<b>Optics:</b>	Polycarbonate Lens
<b>Replaces:</b>	400 Watt Metal Halide	<b>Frequency:</b>	50/60 hz
<b>Color Temp:</b>	4000K   5000K	<b>THD:</b>	< 15%
<b>CRI:</b>	75+	<b>Housing:</b>	Aluminum
<b>IP Rating:</b>	IP65	<b>Fixture Color:</b>	Bronze
<b>Input Voltage:</b>	100V-277V   347V-480V	<b>Mounting:</b>	Arm   Slip Fitter   Trunnion
<b>Operating Temp:</b>	-31°F to +131°F	<b>Dimensions:</b>	13 in X 7 in X 7 in
<b>Rated Life:</b>	50,000 hours	<b>Weight:</b>	29 lbs
		<b>Warranty:</b>	6 years