



Commercial Lighting



Industrial Lighting



Sports Lighting

MLLG-HD-LED-ST Street Light Product Family



**Why
contractors
choose us**



Free Lighting
Plans to ensure
customer
satisfaction



Dedicated
Lighting
Specialist for
each project



Large
inventory of
LED Lights

Table of Contents

	Page Number
- MLLG-HD-LED-ST-30-50-T3	3
- MLLG-HD-LED-ST-50-5-T3	4
- MLLG-HD-LED-ST-75-5-T3	5
- MLLG-HD-LED-ST-120-5-T3	6
- MLLG-HD-LED-ST-165-5-T3	7

30 Watt LED Cobra Head Street Light | 3900 Lumens | Type 3 | 100V-277V



Product Details

SKU: MLLG-HD-LED-ST-30-50-T3

Web ID: 1587

30 Watt LED cobra head street light produces 3900 lumens at 130 lumens/watt and has durable die-cast aluminum heatsink housing. Optics include Type 2 3 4 5 - perfect for street lighting and parking lots. It comes with a 1-10V dimmable 100V-277V LED Driver. Color Temperature is 3000K or 4000K or 5000K. The top of the fixture is solid and smooth to discourage birds from nesting or using it as a platform. The fixture has tool-free access for ease of maintenance. Photocell options include 3-pin and two 7-pin options. You have the option of choosing between 2 surge protection ratings: 10 kVa and 20 kVa. The fixture has a low EPA rating of 0.6 ft sq.

This fixture is mounted on a 2 3/8 in pole. The fixture has internal clamps to secure itself to the pole. It is also IP66 Wet location rated and can operate in temperatures ranging from -40 F to 122 F. This fixture has 1000 hours salt water spray test. The fixture is tough and durable rated at IK08 impact rating.

pStandard Color Temperature is 5000K. 3000K and 4000K are available as well.

/p

Product Specifications

Watts:	30	Dimmable:	1-10V
Lumens:	3900	Beam Angle:	Type 2,3,4,5
Lumens/Watt:	130	Frequency:	50-60Hz
Replaces:	100 Watt Metal Halide	Power Factor:	> .95
Color Temp:	3000K 4000K 5000K	THD:	< 20%
CRI:	70+	Housing:	IP66 - Tool-less access
IP Rating:	IP66	Mounting:	Pole
IK Rating:	IK08	Dimensions:	18 in L X 9 in W X 4 in H
Input Voltage:	100V-277V	Warranty:	5 years
Operating Temp:	-40°F to +122°F		
Rated Life:	100,000 (L70) hours		

50 Watt LED Cobra Head Street Light | 6500 Lumens | Type 3 | 100V-277V



Product Details

SKU: MLLG-HD-LED-ST-50-5-T3

Web ID: 1589

50 Watt LED cobra head street light produces 6500 lumens at 130 lumens/watt and has durable die-cast aluminum heatsink housing. Optics include Type 2 3 4 5 - perfect for street lighting and parking lots. It comes with a 1-10V dimmable 100V-277V LED Driver. Color Temperature is 3000K or 4000K or 5000K. The top of the fixture is solid and smooth to discourage birds from nesting or using it as a platform. The fixture has tool-free access for ease of maintenance. Photocell options include 3-pin and two 7-pin options. You have the option of choosing between 2 surge protection ratings: 10 kVa and 20 kVa. The fixture has a low EPA rating of 0.6 ft sq.

This fixture is mounted on a 2 3/8 in pole. The fixture has internal clamps to secure itself to the pole. It is also IP66 Wet location rated and can operate in temperatures ranging from -40 F to 122 F. This fixture has 1000 hours salt water spray test. The fixture is tough and durable rated at IK08 impact rating.

Standard Color Temperature is 5000K. 3000K and 4000K are available as well.

Product Specifications

Watts:	50	Dimmable:	1-10V
Lumens:	6500	Beam Angle:	Type 2,3,4,5
Lumens/Watt:	130	Frequency:	50-60Hz
Replaces:	150 Watt Metal Halide	Power Factor:	> .95
Color Temp:	3000K 4000K 5000K	THD:	< 20%
CRI:	70+	Housing:	IP66 - Tool-less access
IP Rating:	IP66	Mounting:	Pole
IK Rating:	IK08	Dimensions:	18 in L X 9 in W X 4 in H
Input Voltage:	100V-277V	Weight:	9 lbs
Operating Temp:	-40°F to +122°F	Warranty:	5 years
Rated Life:	100,000 (L70) hours		

75 Watt LED Cobra Head Street Light | 9375 Lumens | Type 3 | 100V-277V



Product Details

SKU: MLLG-HD-LED-ST-75-5-T3

Web ID: 1590

75 Watt LED cobra head street light produces 9375 lumens at 125 lumens/watt and has durable die-cast aluminum heatsink housing. Optics include Type 2 3 4 5 - perfect for street lighting and parking lots. It comes with a 1-10V dimmable 100V-277V LED Driver. Color Temperature is 3000K or 4000K or 5000K. The top of the fixture is solid and smooth to discourage birds from nesting or using it as a platform. The fixture has tool-free access for ease of maintenance. Photocell options include 3-pin and two 7-pin options. You have the option of choosing between 2 surge protection ratings: 10 kVa and 20 kVa. The fixture has a low EPA rating of 0.6 ft sq.

This fixture is mounted on a 2 3/8 in pole. The fixture has internal clamps to secure itself to the pole. It is also IP66 Wet location rated and can operate in temperatures ranging from -40 F to 122 F. This fixture has 1000 hours salt water spray test. The fixture is tough and durable rated at IK08 impact rating.

Standard Color Temperature is 5000K. 3000K and 4000K are available as well.

Product Specifications

Watts:	75	Dimmable:	1-10V
Lumens:	9375	Beam Angle:	Type 2,3,4,5
Lumens/Watt:	125	Frequency:	50-60Hz
Replaces:	250 Watt Metal Halide	Power Factor:	> .95
Color Temp:	3000K 4000K 5000K	THD:	< 20%
CRI:	70+	Housing:	IP66 - Tool-less access
IP Rating:	IP66	Mounting:	Pole
IK Rating:	IK08	Dimensions:	18 in L X 9 in W X 4 in H
Input Voltage:	100V-277V	Weight:	9.5 lbs
Operating Temp:	-40°F to +122°F	Warranty:	5 years
Rated Life:	100,000 (L70) hours		

120 Watt LED Cobra Head Street Light | 15600 Lumens | Type 3 | 100V-277V



Product Details

SKU: MLLG-HD-LED-ST-120-5-T3

Web ID: 1591

120 Watt LED cobra head street light produces 15600 lumens at 130 lumens/watt and has durable die-cast aluminum heatsink housing. Optics include Type 2 3 4 5 - perfect for street lighting and parking lots. It comes with a 1-10V dimmable 100V-277V LED Driver. Color Temperature is 4000K or 5000K. The top of the fixture is solid and smooth to discourage birds from nesting or using it as a platform. The fixture has tool-free access for ease of maintenance. Photocell options include 3-pin and two 7-pin options. You have the option of choosing between 2 surge protection ratings: 10 kVa and 20 kVa. The fixture has low EPA rating of 0.6 ft sq.

This fixture is mounted on a 2 3/8 in pole. The fixture has internal clamps to secure itself to the pole. It is also IP66 Wet location rated and can operate in temperatures ranging from -40 F to 122 F. This fixture has 1000 hours salt water spray test. The fixture is tough and durable rated at IK08 impact rating.

Standard Color Temperature is 5000K. 3000K and 4000K are available as well.

Product Specifications

Watts:	120	Dimmable:	1-10V
Lumens:	15600	Beam Angle:	Type 2,3,4,5
Lumens/Watt:	130	Frequency:	50-60Hz
Replaces:	400 Watt Metal Halide	Power Factor:	> .95
Color Temp:	4000K 5000K	THD:	< 20%
CRI:	70+	Housing:	IP66 - Tool-less access
IP Rating:	IP66	Mounting:	Pole
IK Rating:	IK08	Dimensions:	18 in L X 9 in W X 4 in H
Input Voltage:	100V-277V	Weight:	11.5 lbs
Operating Temp:	-40°F to +122°F	Warranty:	5 years
Rated Life:	100,000 (L70) hours		

165 Watt LED Cobra Head Street Light | 21450 Lumens | Type 3 | 100V-277V



Product Details

SKU: MLLG-HD-LED-ST-165-5-T3

Web ID: 1672

165 Watt LED cobra head street light produces 21450 lumens at 130 lumens/watt and has durable die-cast aluminum heatsink housing. Optics include Type 2 3 4 5 - perfect for street lighting and parking lots. It comes with a 1-10V dimmable 100V-277V LED Driver. Color Temperature is 3000K or 4000K or 5000K. The top of the fixture is solid and smooth to discourage birds from nesting or using it as a platform. The fixture has tool-free access for ease of maintenance. Photocell options include 3-pin and two 7-pin options. You have the option of choosing between 2 surge protection ratings: 10 kVa and 20 kVa.

Fixture has a low EPA rating of 0.6 ft sq. This fixture is mounted on a 2 3/8 in pole. The fixture has internal clamps to secure itself to the pole. It is also IP66 Wet location rated and can operate in temperatures ranging from -40 F to 122 F. This fixture has 1000 hours salt water spray test. The fixture is tough and durable rated at IK08 impact rating.

Standard Color Temperature is 5000K. 3000K and 4000K are available as well.

Product Specifications

Watts:	165	Dimmable:	1-10V
Lumens:	21450	Beam Angle:	Type 2,3,4,5
Lumens/Watt:	130	Frequency:	50-60Hz
Replaces:	400 Watt Metal Halide	Power Factor:	> .95
Color Temp:	3000K 4000K 5000K	THD:	< 20%
CRI:	70+	Housing:	IP66 - Tool-less access
IP Rating:	IP66	Mounting:	Pole
IK Rating:	IK08	Dimensions:	18 in L X 9 in W X 4 in H
Input Voltage:	100V-277V	Weight:	11.75 lbs
Operating Temp:	-40°F to +122°F	Warranty:	5 years
Rated Life:	100,000 (L70) hours		