



Commercial Lighting



Industrial Lighting



Sports Lighting

## MLLG-LED-CAN Canopy Light Product Family



**Why  
contractors  
choose us**



Free Lighting  
Plans to ensure  
customer  
satisfaction



Dedicated  
Lighting  
Specialist for  
each project



Large  
inventory of  
LED Lights

# Table of Contents

	Page Number
- MLLG-LED-CANLB-120-CC	3
- MLLG-LED-CANLBR-100-CC	4
- MLLG-LN-LED-CANR-60-50	5
- MLLG-LN-LED-CANR-60-50-MS	6
- MLLG-LN-LED-CANLB-80-CC	7
- MLLG-LN-LED-CAN-150-50	8
- MLLG-WD-LED-CANG-95-50	9
- MLLG-WD-LED-CANG-120-50	10
- MLLG-LED-CANS2-30-50	11
- MLLG-LED-CANS2-20-50	12

## 36 / 60 / 90 / 120 Watt Adjustable LED Canopy Light | 4860 to 16200 Lumens



### Product Details

**SKU:** MLLG-LED-CANLB-120-CC

**Web ID:** 1958

36 | 60 | 90 | 120 wattage adjustable LED canopy fixture produces 4860 | 8100 | 12150 | 16200 lumens at 135 lumens / watt replaces 250 | 400 Watt Metal Halide. It is designed with die-cast aluminum heat sink housing and finished with an anti-corrosion white powder coat. Lens is tough vandal-proof clear acrylic.

Fixture comes with a 100V-277V LED driver. Color temperature is field adjustable: 3500K or 4000K or 5000K and light distribution is 120°. The fixture is surface-mounted and contains all the parts you need to do a quick and easy install. Fixture is Wet Location IP65 rated and IK08 Impact Rating. Comes with a 6 kVa surge protector.

### Product Specifications

<b>Watts:</b>	36   60   90   120	<b>Dimmable:</b>	No
<b>Lumens:</b>	4860   8100   12150   16200	<b>Beam Angle:</b>	120°
<b>Lumens/Watt:</b>	135	<b>Frequency:</b>	50-60Hz
<b>Replaces:</b>	250   400 Watt Metal Halide	<b>Power Factor:</b>	> .90
<b>Color Temp:</b>	3500K   4000K   5000K	<b>THD:</b>	< 20%
<b>CRI:</b>	70+	<b>Housing:</b>	Die-Cast Aluminum
<b>IP Rating:</b>	IP65	<b>Fixture Color:</b>	White
<b>IK Rating:</b>	IK08	<b>Mounting:</b>	Pendant   Surface
<b>Input Voltage:</b>	100V-277V	<b>Dimensions:</b>	14.5 in X 14.5 in X 2.5 in
<b>Surge Protection:</b>	6kV line-line, 10kV line-earth	<b>Weight:</b>	8.6 lbs
<b>Operating Temp:</b>	-22°F to +122°F	<b>Warranty:</b>	5 years
<b>Rated Life:</b>	150,000 (L70) hours		

### Product Options

#### Pendant Bracket

Pendant Bracket  
Adapter

## 30 / 50 / 75 / 100 Watt Adjustable LED Canopy Light | 4200 to 14000 Lumens



### Product Details

**SKU:** MLLG-LED-CANLBR-100-CC

**Web ID:** 2121

30 | 50 | 75 | 100 wattage adjustable LED canopy fixture produces 4200 | 7000 | 10500 | 14000 lumens at 140 lumens/watt replaces 250 | 400 Watt Metal Halide. It is designed with die-cast aluminum heat sink housing and finished with an anti-corrosion white powder coat. Lens is tough vandal-proof clear acrylic.

Light includes 1400 lumens of 5000k uplight ( CCT not adjustable for uplight ). There is a switch to disable the uplight feature located under the center cap on the face of the fixture

Fixture comes with a 100V-277V LED driver. Color temperature is field adjustable: 3000K or 4000K or 5000K and light distribution is 120 . The fixture is surface-mounted and contains all the parts you need to do a quick and easy install. Fixture is Wet Location IP65 rated and IK08 Impact Rating. Comes with a 6 kVa surge protector.

### Product Specifications

<b>Watts:</b>	30   50   75   100	<b>Dimmable:</b>	No
<b>Lumens:</b>	4200   7000   10500   14000	<b>Beam Angle:</b>	120°
<b>Lumens/Watt:</b>	140	<b>Optics:</b>	Polycarbonate Lens
<b>Replaces:</b>	250   400 Watt Metal Halide	<b>Frequency:</b>	50-60Hz
<b>Color Temp:</b>	3000K   4000K   5000K	<b>Power Factor:</b>	> .90
<b>CRI:</b>	70+	<b>THD:</b>	< 20%
<b>IP Rating:</b>	IP65	<b>Housing:</b>	Die-Cast Aluminum
<b>IK Rating:</b>	IK08	<b>Fixture Color:</b>	White
<b>Input Voltage:</b>	100V-277V	<b>Mounting:</b>	Pendant   Surface
<b>Surge Protection:</b>	6kV line-line, 10kV line-earth	<b>Dimensions:</b>	12.7 in D X 3.5 in H
<b>Operating Temp:</b>	-22°F to +113°F	<b>Weight:</b>	6 lbs
<b>Rated Life:</b>	100,000 (L70) hours	<b>Warranty:</b>	5 years

### Product Options

#### Pendant Bracket

Pendant Bracket  
Adapter

## 30 / 40 / 60 Watt Adjustable Canopy Light | 3900 / 5200 / 7800 Lumens | 5000K



### Product Details

**SKU:** MLLG-LN-LED-CANR-60-50

**Web ID:** 1563

30 | 40 | 60 wattage adjustable LED round canopy fixture produces 3900 | 5200 | 7800 lumens at 130 lumens/watt and replaces 250 Watt Metal Halide. It is designed with die-cast aluminum heatsink housing and finished with an anti-corrosion white powder coat. Lens is tough frosted acrylic.

Fixture comes with a 100V-277V 1-10V dimmable driver as well as a 10 kVa built-in surge protector. Color temperature is 5000K and light distribution is 130°. The fixture is surface-mounted and has 1/2 inch coin plugs for easy conduit access. Fixture is Wet Location IP65 rated.

### Product Specifications

<b>Watts:</b>	30   40   60	<b>Dimmable:</b>	1-10V
<b>Lumens:</b>	3900   5200   7800	<b>Beam Angle:</b>	130°
<b>Lumens/Watt:</b>	130	<b>Frequency:</b>	50-60Hz
<b>Replaces:</b>	250 Watt Metal Halide	<b>Power Factor:</b>	> .90
<b>Color Temp:</b>	5000K	<b>THD:</b>	< 20%
<b>CRI:</b>	70+	<b>Housing:</b>	Die-Cast Aluminum
<b>IP Rating:</b>	IP65	<b>Fixture Color:</b>	White
<b>Input Voltage:</b>	100V-277V	<b>Mounting:</b>	Pendant   Surface
<b>Operating Temp:</b>	-40°F to +113°F	<b>Dimensions:</b>	12.2 in D X 5.5 in H
<b>Rated Life:</b>	50,000 (L70) hours	<b>Weight:</b>	6.5 lbs
		<b>Warranty:</b>	5 years

## 30 / 40 / 60 Watt Adjustable LED Canopy Light | 3900 to 7800 Lumens | 5000K



### Product Details

**SKU:** MLLG-LN-LED-CANR-60-50-MS

**Web ID:** 1910

30 | 40 | 60 wattage adjustable LED round canopy fixture produces 3900 | 5200 | 8400 lumens at 140 lumens/watt and replaces 250 Watt Metal Halide. It is designed with die-cast aluminum heatsink housing and finished with an anti-corrosion white powder coat. Lens is tough frosted acrylic.

Fixture comes with a 100V-277V 1-10V dimmable driver as well as a 10 kVa built-in surge protector. Color temperature is 5000K and light distribution is 130°. The fixture is surface-mounted and has 1/2 inch coin plugs for easy conduit access. Fixture is Wet Location IP65 rated.

### Product Specifications

<b>Watts:</b>	30   40   60	<b>Dimmable:</b>	1-10V
<b>Lumens:</b>	3900   5200   8400	<b>Beam Angle:</b>	130°
<b>Lumens/Watt:</b>	140	<b>Frequency:</b>	50-60Hz
<b>Replaces:</b>	250 Watt Metal Halide	<b>Power Factor:</b>	> .90
<b>Color Temp:</b>	5000K	<b>THD:</b>	< 20%
<b>CRI:</b>	70+	<b>Housing:</b>	Die-Cast Aluminum
<b>IP Rating:</b>	IP65	<b>Fixture Color:</b>	White
<b>Input Voltage:</b>	100V-277V	<b>Mounting:</b>	Pendant   Surface
<b>Operating Temp:</b>	-40°F to +113°F	<b>Dimensions:</b>	12.2 in D X 5.5 in H
<b>Rated Life:</b>	50,000 (L70) hours	<b>Warranty:</b>	5 years

## 40 Watt to 80 Watt Power and Color Adjustable LED Canopy Light



### Product Details

**SKU:** MLLG-LN-LED-CANLB-80-CC

**Web ID:** 1905

40 | 60 | 80 Wattage adjustable LED canopy fixture produces 5200 | 7800 | 10400 lumens at 130 lumens/watt replaces 150 | 250 Watt Metal Halide. It is designed with die-cast aluminum heat sink housing and finished with an anti-corrosion white powder coat. Lens is tough vandal-proof clear acrylic.

Fixture comes with a 100V-277V LED driver. Color temperature is adjustable: 3500K or 4000K or 5000K and light distribution is 150°. The fixture is surface-mounted and contains all the parts you need to do a quick and easy install. 1/2 inch coin plugs for easy conduit access. Fixture is Wet Location IP65 rated.

### Product Specifications

<b>Watts:</b>	40   60   80	<b>Dimmable:</b>	1-10V
<b>Lumens:</b>	5200   7800   10400	<b>Beam Angle:</b>	150°
<b>Lumens/Watt:</b>	130	<b>Frequency:</b>	50-60Hz
<b>Replaces:</b>	150   250 Watt Metal Halide	<b>Power Factor:</b>	> .90
<b>Color Temp:</b>	3500K   4000K   5000K	<b>THD:</b>	< 20%
<b>CRI:</b>	80+	<b>Housing:</b>	Die-Cast Aluminum
<b>IP Rating:</b>	IP65	<b>Fixture Color:</b>	Bronze
<b>Input Voltage:</b>	100V-277V	<b>Mounting:</b>	Pendant   Surface
<b>Operating Temp:</b>	-4°F to +113°F	<b>Dimensions:</b>	10 in X 10 in X 2.75 in
<b>Rated Life:</b>	50,000 (L70) hours	<b>Weight:</b>	5 lbs
		<b>Warranty:</b>	5 years

### Product Options

**Motion Sensor**

No Motion Sensor

Motion Sensor



## 150 Watt LED Canopy Light | 19500 Lumens | 5000K | 100-277



### Product Details

**SKU:** MLLG-LN-LED-CAN-150-50

**Web ID:** 1560

150 Watt LED canopy fixture replaces 400 Watt Metal Halide and produces 19500 lumens at 130 lumens/watt and is designed with die-cast aluminum heat sink housing and finished with an anti-corrosion white powder coat finish. Lens is tough vandal-proof clear acrylic.

Fixture comes with a 100V-277V driver. Color temperature is 5000K and light distribution is 120°. The fixture is pendant or surface mounted. They can operate in temperatures between -4 F to 113 F and are IP65 rated and UL Listed for Wet Locations.

### Product Specifications

<b>Watts:</b>	150	<b>Dimmable:</b>	No
<b>Lumens:</b>	19500	<b>Beam Angle:</b>	120°
<b>Lumens/Watt:</b>	130	<b>Frequency:</b>	50-60Hz
<b>Replaces:</b>	400 Watt Metal Halide	<b>Power Factor:</b>	> .90
<b>Color Temp:</b>	5000K	<b>THD:</b>	< 20%
<b>CRI:</b>	80+	<b>Housing:</b>	Die-Cast Aluminum
<b>IP Rating:</b>	IP65	<b>Fixture Color:</b>	White
<b>Input Voltage:</b>	100V-277V	<b>Mounting:</b>	Pendant   Recessed
<b>Operating Temp:</b>	-4°F to +113°F	<b>Dimensions:</b>	15 in X 15 in X 3 in
<b>Rated Life:</b>	50,000 (L70) hours	<b>Weight:</b>	14 lbs
		<b>Warranty:</b>	5 years



## 95 Watt LED Canopy Light | 12721 Lumens | 5000K | 100-277V



### Product Details

**SKU:** MLLG-WD-LED-CANG-95-50

**Web ID:** 1971

95 Watt surface mount LED canopy fixture produces 12721 lumens at 134 lumens/watt replacing 250 Watt Metal Halide and has a die-cast aluminum heat sink body. IP65 rating protects this fixture from water and dust.

Canopy fixture comes with a wide-angle 111 beam angle. It comes with a 100V-277V driver. Color temperature is 5000K. The fixture is white. This fixture is surface-mounted to the bottom of a canopy structure and will provide years of maintenance-free lighting.

### Product Specifications

<b>Watts:</b>	95	<b>Dimmable:</b>	1-10V
<b>Lumens:</b>	12721	<b>Beam Angle:</b>	111°
<b>Lumens/Watt:</b>	134	<b>Frequency:</b>	50-60Hz
<b>Replaces:</b>	250 Watt Metal Halide	<b>Power Factor:</b>	> .90
<b>Color Temp:</b>	5000K	<b>THD:</b>	< 20%
<b>CRI:</b>	70+	<b>Housing:</b>	Die-Cast Aluminum
<b>IP Rating:</b>	IP65	<b>Fixture Color:</b>	White
<b>Input Voltage:</b>	100V-277V	<b>Mounting:</b>	Surface
<b>Operating Temp:</b>	-22°F to +113°F	<b>Dimensions:</b>	17.13 in X 17.13 in X 4.13 in
<b>Rated Life:</b>	50,000 (L70) hours	<b>Weight:</b>	9 lbs
		<b>Warranty:</b>	5 years

## 120 Watt LED Canopy Light | 16086 Lumens | 5000K | 100-277V



### Product Details

**SKU:** MLLG-WD-LED-CANG-120-50

**Web ID:** 1972

120 Watt surface mount LED canopy fixture produces 16086 lumens at 134 lumens/watt replacing 400 Watt Metal Halide and has a die-cast aluminum heat sink body. IP65 rating protects this fixture from water and dust.

Canopy fixture comes with a wide-angle 109 beam angle. It comes with a 100V-277V driver. Color temperature is 5000K. The fixture is white. This fixture is surface mounted to the bottom of a canopy structure and will provide years of maintenance-free lighting.

### Product Specifications

<b>Watts:</b>	120	<b>Dimmable:</b>	1-10V
<b>Lumens:</b>	16086	<b>Beam Angle:</b>	109°
<b>Lumens/Watt:</b>	134	<b>Frequency:</b>	50-60Hz
<b>Replaces:</b>	400 Watt Metal Halide	<b>Power Factor:</b>	> .90
<b>Color Temp:</b>	5000K	<b>THD:</b>	< 20%
<b>CRI:</b>	70+	<b>Housing:</b>	Die-Cast Aluminum
<b>IP Rating:</b>	IP65	<b>Fixture Color:</b>	White
<b>Input Voltage:</b>	100V-277V	<b>Mounting:</b>	Surface
<b>Operating Temp:</b>	-22°F to +113°F	<b>Dimensions:</b>	17.13 in X 17.13 in X x 4.13 in
<b>Rated Life:</b>	50,000 (L70) hours	<b>Weight:</b>	9 lbs
		<b>Warranty:</b>	5 years

## 30 Watt Canopy Light | 3780 Lumens | 5000K | 100-277V



### Product Details

**SKU:** MLLG-LED-CANS2-30-50

**Web ID:** 1467

30 Watt LED canopy fixture produces 3780 lumens at 126 lumens/watt replacing 150 Watt Metal Halide and is designed with rust-proof die-cast aluminum housing and has a powder coat finish. The lens is clear prismatic poly-carbonate and UV stabilized.

Canopy fixture comes with 100V-277V 1-10V dimmable driver. 5000K color temperature and BRONZE finish. The fixture is surface-mounted. 1/2 inch coin plugs in each quadrant for easy conduit access. Fixture is IP65 rated and UL Listed for Wet Locations.

### Product Specifications

<b>Watts:</b>	30	<b>Dimmable:</b>	1-10V
<b>Lumens:</b>	3780	<b>Beam Angle:</b>	120°
<b>Lumens/Watt:</b>	126	<b>Frequency:</b>	50-60Hz
<b>Replaces:</b>	150 Watt Metal Halide	<b>Power Factor:</b>	> .90
<b>Color Temp:</b>	5000K	<b>THD:</b>	< 20%
<b>CRI:</b>	75+	<b>Housing:</b>	Die-Cast Aluminum
<b>IP Rating:</b>	IP65	<b>Fixture Color:</b>	Bronze
<b>Input Voltage:</b>	100V-277V	<b>Mounting:</b>	Surface
<b>Operating Temp:</b>	-31°F to +131°F	<b>Dimensions:</b>	10.5 in L X 10.5 in W X 4.0 in H
<b>Rated Life:</b>	50,000 hours	<b>Warranty:</b>	6 years

## 20 Watt Canopy Light | 2520 Lumens | 5000K | 100-277V



### Product Details

**SKU:** MLLG-LED-CANS2-20-50

**Web ID:** 880

20 Watt LED canopy fixture produces 2520 lumens at 126 lumens/watt replacing 100 Watt Metal Halide and is designed with rust-proof die-cast aluminum housing and has a powder coat finish. The lens is clear prismatic poly-carbonate and UV stabilized.

Canopy fixture comes with 100V-277V 1-10V dimmable driver. 5000K color temperature and bronze finish. The fixture is surface-mounted. 1/2 inch coin plugs in each quadrant for easy conduit access. Fixture is IP65 rated and UL Listed for Wet Locations.

### Product Specifications

<b>Watts:</b>	20	<b>Dimmable:</b>	1-10V
<b>Lumens:</b>	2520	<b>Beam Angle:</b>	120°
<b>Lumens/Watt:</b>	126	<b>Frequency:</b>	50-60Hz
<b>Replaces:</b>	100 Watt Metal Halide	<b>Power Factor:</b>	> .90
<b>Color Temp:</b>	5000K	<b>THD:</b>	< 20%
<b>CRI:</b>	75+	<b>Housing:</b>	Die-Cast Aluminum
<b>IP Rating:</b>	IP65	<b>Fixture Color:</b>	Bronze
<b>Input Voltage:</b>	100V-277V	<b>Mounting:</b>	Surface
<b>Operating Temp:</b>	-31°F to +131°F	<b>Dimensions:</b>	10.5 in L X 10.5 in W X 4.0 in H
<b>Rated Life:</b>	50,000 hours	<b>Warranty:</b>	6 years