







MLLG-LED-CAN LED Flush Mounted Product Family





Why contractors choose us

Free Lighting
Plans to ensure
customer
satisfaction

Dedicated Lighting Specialist for each project Large inventory of LED Lights

Table of Contents

	Page Number
- MLLG-AL-LED-CAN12MV-20-CC-NK	3
- MLLG-AL-LED-CAN14MV-21-CC-NK	4
- MLLG-AL-LED-CAN16MV-24-CC-NK	5
- MLLG-AL-LED-CAN14EMB-21-CC	6



20 Watt 12 In LED Flush Mounted Ceiling Light | 1400 Lumens



Product Details

SKU: MLLG-AL-LED-CAN12MV-20-CC-NK

Web ID: 1636

20 Watts DOUBLE RING Flush Mounted LED Ceiling Light has a modern and stylish appearance. Lumens is 1400 and Lumens Per Watt is 70. Smooth dimming is provided ranging from 10% to 100% using modern LED dimmers. 120 beam angle provides uniform lighting.

You can select 3000K or 4000K or 5000K color temperatures using the onboard toggle switch. This fixture has a BRUSHED NICKEL finish. LED Driver is 100V-277V. Installation is simple. Attach the mounting bracket to the outlet box connect the wires and fix the fixture body on the mounting bracket.

Product Specifications

Watts:	20	Dimmable:	Triac	
Lumens:	1400	Beam Angle:	120°	
Lumens/Watt:	70	Frequency: 50 / 60 hz		
Replaces:	75W Incandescent	Housing: Stainless Steel with Acrylic Lens		
Color Temp:	3000K 4000K 5000K	Fixture Color: Brushed Nickel		
CRI:	80+	Mounting:	Surface	
Input Voltage:	100V-277V	Dimensions:	12 in round	
Operating Temp:	-4°F to +131°F	Weight: 2 lbs		
Rated Life:	50,000 hours	Warranty:	5 years	



21 Watt 14 Inch LED Flush Mounted Ceiling Light | 1460 Lumens



Product Details

SKU: MLLG-AL-LED-CAN14MV-21-CC-NK

Web ID: 1637

21 Watts DOUBLE RING Flush Mounted LED Ceiling Light has a modern and stylish appearance. Lumens is 1460 and Lumens Per Watt is 70. Smooth dimming is provided ranging from 10% to 100% using modern LED dimmers. 150 beam angle provides uniform lighting.

You can select 3000K or 4000K or 5000K color temperatures using the onboard toggle switch. This fixture has a BRUSHED NICKEL finish. LED Driver is 100V-277V. Installation is simple. Attach the mounting bracket to the outlet box connect the wires and fix the fixture body on the mounting bracket. All screws wire nuts and all installation accessories are provided.

Product Specifications

Watts:	21	Dimmable: Triac	
Lumens:	1460	Beam Angle:	120°
Lumens/Watt:	70	Frequency:	50 / 60 hz
Replaces:	75W Incandescent	Housing: Stainless Steel with Acrylic Lens	
Color Temp:	3000K 4000K 5000K	Fixture Color:	Brushed Nickel
CRI:	80+	Mounting:	Surface
Input Voltage:	100V-277V	Dimensions:	14 in round
Operating Temp:	-4°F to +131°F	Weight: 2.5 lbs	
Rated Life:	50,000 hours	Warranty:	5 years



24 Watt 16 Inch LED Flush Mounted Ceiling Light | 1700 Lumens



Product Details

SKU: MLLG-AL-LED-CAN16MV-24-CC-NK

Web ID: 1796

24 Watts DOUBLE RING Flush Mounted LED Ceiling Light has a modern and stylish appearance. Lumens is 1700 and Lumens Per Watt is 71. Smooth dimming is provided ranging from 10% to 100% using modern LED dimmers. 150 beam angle provides uniform lighting.

You can select 3000K or 4000K or 5000K color temperatures using the onboard toggle switch. This fixture has a BRUSHED NICKEL finish. LED Driver is 100V-277V. Installation is simple. Attach the mounting bracket to the outlet box connect the wires and fix the fixture body on the mounting bracket. All screws wire nuts and all installation accessories are provided.

Product Specifications

Watts:	24	Dimmable:	able: Triac	
Lumens:	1700	Beam Angle:	120°	
Lumens/Watt:	71	Frequency:	50 / 60 hz	
Replaces:	75W Incandescent	Housing: Stainless Steel with Acrylic Lens		
Color Temp:	3000K 4000K 5000K	Fixture Color:	Brushed Nickel	
CRI:	80+	Mounting:	Surface	
Input Voltage:	100V-277V	Dimensions:	16 in round	
Operating Temp:	-4°F to +131°F	Weight: 2.5 lbs		
Rated Life:	50,000 hours	Warranty:	5 years	



21 Watt 14 Inch LED Flush Mounted Ceiling Light | 1470 Lumens



Product Details

SKU: MLLG-AL-LED-CAN14EMB-21-CC

Web ID: 1639

21 Watts DOUBLE RING Flush Mounted LED Ceiling Light WITH BACK-UP BATTERY has a modern and stylish appearance. Lumens is 1470 and Lumens Per Watt is 70. The built-in back-up battery provides 90 minutes of power and takes 8 hours to fully charge back up. Smooth dimming is provided ranging from 10% to 100% using modern LED dimmers. 120 beam angle provides uniform lighting.

You can select 3000K or 4000K or 5000K color temperatures using the onboard toggle switch. This fixture has a BRUSHED NICKEL or OIL BRONZE finish. LED Driver is 100V-277V. Installation is simple. Link the LED Emergency Controller to the backup battery connect the wires and screw the fixture to the outlet box.

Product Specifications

Watts:	21	Dimmable:	Triac	
Lumens:	1470	Beam Angle:	120°	
Lumens/Watt:	70	Frequency: 50 / 60 hz		
Replaces:	75W Incandescent	Housing: Stainless Steel with Acrylic Lens		
Color Temp:	3000K 4000K 5000K	Fixture Color: Brushed Nickel Oil Rubbed Bronze		
CRI:	80+	Mounting: Surface		
Input Voltage:	100V-277V	Dimensions: 14 in D X 4.5 in H		
Operating Temp:	-32°F to +113°F	Weight: 3.75 lbs		
Rated Life:	50,000 hours	Warranty:	5 years	

Product Options

						_
Ci	iv:	tı	ırα	Сi	nis	h

Brushed Nickel Oil Rubbed Bronze