



Commercial Lighting



Industrial Lighting



Sports Lighting

MLLG-LED-Cobra-Head Light Product Family



**Why
contractors
choose us**



Free Lighting
Plans to ensure
customer
satisfaction



Dedicated
Lighting
Specialist for
each project



Large
inventory of
LED Lights

Table of Contents

	Page Number
- MLLG-WD-LED-COBRA-100-5	3
- MLLG-WD-LED-COBRA-150-5	4

100 Watt LED Cobra Head Street Light | 15000 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-WD-LED-COBRA-100-5

Web ID: 1956

100 Watt LED cobra head street light produces 15000 lumens at 150 lumens/watt replacing 400 Watt Metal Halide and has durable die-cast aluminum housing. Optics include Type 3 - perfect for street lighting and parking lots. It comes with a driver at 100V-277V. Color Temperature is 5000K. Photocell is available if you need one.

This fixture is mounted on a 2 3/8 in pole. The fixture has internal clamps to secure itself to the pole. Access to the fixture is tool-free and power-off protection ensures safety during installation and maintenance. It is IP65 Wet location rated and can operate in temperatures ranging from -22 F to 113 F.

Optional Accessories:

MLLG-WD-COBRA-SF - 90 Degree Slip Fitter with 3.13 inch inside diameter

Product Specifications

Watts:	100	Beam Angle:	Type 3
Lumens:	15000	Frequency:	50-60Hz
Lumens/Watt:	150	Power Factor:	.95
Replaces:	400 Watt Metal Halide	THD:	< 20%
Color Temp:	5000K	Housing:	IP65 - Aluminum Alloy and PC Lens
CRI:	70+	Mounting:	Pole
IP Rating:	IP65	Dimensions:	18.67 in L X 10.8 in W
Input Voltage:	100V-277V	Weight:	10 lbs
Operating Temp:	-22°F to +113°F	Warranty:	5 years
Rated Life:	70,000 hours		

Product Options

Photocell	
Photocell	

150 Watt LED Cobra Head Street Light | 22700 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-WD-LED-COBRA-150-5

Web ID: 1957

150 Watt LED cobra head street light produces 22700 lumens at 151 lumens/watt replacing 400 Watt Metal Halide and has durable die-cast aluminum housing. Optics include Type 3 - perfect for street lighting and parking lots. It comes with a driver at 100V-277V. Color Temperature is 5000K. Photocell is available if you need one.

This fixture is mounted on a 2 3/8 in pole. The fixture has internal clamps to secure itself to the pole. Access to the fixture is tool free and power-off protection ensures safety during installation and maintenance. It is IP65 Wet location rated and can operate in temperatures ranging from -22 F to 113 F.

Optional Accessories:

MLLG-WD-COBRA-SF - 90 Degree Slip Fitter with 3.13 inch inside diameter

Product Specifications

Watts:	150	Beam Angle:	Type 3
Lumens:	22700	Frequency:	50-60Hz
Lumens/Watt:	151	Power Factor:	.95
Replaces:	400 Watt Metal Halide	THD:	< 20%
Color Temp:	5000K	Housing:	IP65 - Aluminum Alloy and PC Lens
CRI:	70+	Mounting:	Pole
IP Rating:	IP65	Dimensions:	18.67 in L X 10.8 in W
Input Voltage:	100V-277V	Weight:	10 lbs
Operating Temp:	-22°F to +113°F	Warranty:	5 years
Rated Life:	70,000 hours		

Product Options

Photocell	
Photocell	