



Commercial Lighting



Industrial Lighting



Sports Lighting

MLLG-LED-HBC High Bay Product Family



**Why
contractors
choose us**



Free Lighting
Plans to ensure
customer
satisfaction



Dedicated
Lighting
Specialist for
each project



Large
inventory of
LED Lights

Table of Contents

	Page Number
- MLLG-LED-HBC-200-[Color]-120	3
- MLLG-LED-HB4-200-CC-120	4
- MLLG-LED-HB3-200-50-120-[C]	5
- MLLG-LED-HB3-100-50-120	6

100 / 120 / 150 / 200 Watt Adjustable UFO High Bay | 15000 to 30000 Lumens



Product Details

SKU: MLLG-LED-HBC-200-[Color]-120

Web ID: 1536

100 | 120 | 150 | 200 Wattage Adjustable UFO high bay produces 15000 | 18000 | 22500 | 30000 lumens at 150 lumens/watt and replaces 250 | 400 Watt Metal Halide. It is equipped with 1-10V dimmable drivers. A white aluminum die-cast heat sink provides great heat dissipation. Available in voltage: 100V-277V and Color Temperature: 4000K or 5000K. Additional options include a motion sensor kit for higher energy savings. Operates in temperatures from -22 F to 122 F.

Commonly used in distribution centers warehouse facilities auto shops and retail spaces that require high ceiling lights.

Choose a Polycarbonate 120 Frosted (std) / 60 90 (opt) lens. Includes built-in 4 kVa surge protection. Mounting options are: Eye-Hook (std) or Pendant. These high bays are IP65 Wet location rated and High Impact IK08 rated.

Motion Sensor Operation: If purchasing a motion sensor please note that a remote control is also required. This will allow you to change the operation of the motion sensor to suit your needs.

Product Specifications

[Download Motion Sensor Setup Guide](#)

Watts:	100 120 150 200	Dimmable:	1-10V
Lumens:	15000 18000 22500 30000	Beam Angle:	120° Frosted (std) / 60° 90° (opt)
Lumens/Watt:	150	Frequency:	50 / 60 hz
Replaces:	250 400 Watt Metal Halide	Power Factor:	.90
Color Temp:	4000K 5000K	THD:	20% Max
CRI:	80+	Housing:	Die-Cast Aluminum
IP Rating:	IP65	Fixture Color:	White
IK Rating:	IK08	Mounting:	Eye-Hook (std) Pendant
Input Voltage:	100V-277V	Dimensions:	10.67 in X 7.32 in
Surge Protection:	4kVa line-line, 4kVa line-earth	Weight:	8 lbs
Operating Temp:	-22°F to +122°F	Warranty:	5 years
Rated Life:	170,000 (L70) hours		

Product Options

Lens	Dome	Mounting	Motion Sensor	Remote Control
120 Degree Frosted 120 Degree Clear Lens 60 Degree Optic 90 Degree Optic	Acrylic Dome	Eye Hook Mount Pendant Mount Adjustable Ceiling Mount	Motion Sensor (Dims to 10% - not off)	No Motion Sensor Remote Control Motion Sensor Remote Control - Qty 1 Motion Sensor Remote Control - Qty 2 Motion Sensor Remote Control - Qty 3

120 / 160 / 200 Watt Adjustable LED UFO Fixture | 18000 to 30000 Lumens



Product Details

SKU: MLLG-LED-HB4-200-CC-120

Web ID: 2043

120 | 160 | 200 Watts Field Changeable 4000K or 5000K Color Adjustable 60 90 120 field adjustable Beam Adjustable UFO LED light produces 18000 | 24000 | 30000 lumens (based on your selection) at 150 lumens/watt and replaces 400 Watt Metal Halide.

White aluminum die-cast heat sink provides optimal heat dissipation. Available in voltage: 100V-277V. Additional options include a motion sensor kit for higher energy savings. Operates in temperatures from -22 F to 122 F.

It comes equipped with a Polycarbonate 60 90 120 field adjustable lens. Includes built-in 4 kVa surge protection. Mounting options are: Eye-Hook (std) or Pendant or Surface. These high bay fixtures are IP65 Wet location rated and High Impact IK08 rated.

Field Selectable Power Options (Default is 200 Watts)

120 Watts - 18000 lumens 160 Watts - 24000 lumens 200 Watts - 30000 lumens

Field Selectable Color Temperature Options

4000K or 5000K

Field Selectable Beam Angles

60 or 90 or 120

Motion Sensor Operation: If purchasing a motion sensor please note that a remote control is also required. This will allow you to change the operation of the motion sensor to be suit your needs.

Product Specifications

Watts:	120 160 200	Dimmable:	No
Lumens:	18000 24000 30000	Beam Angle:	60° 90° 120° field adjustable
Lumens/Watt:	150	Optics:	Polycarbonate Lens
Replaces:	400 Watt Metal Halide	Frequency:	50 / 60 hz
Color Temp:	4000K 5000K	Power Factor:	.95
CRI:	80+	THD:	20% Max
IP Rating:	IP65	Housing:	Aluminum Alloy
IK Rating:	IK08	Fixture Color:	White
Input Voltage:	100V-277V	Mounting:	Eye-Hook (std) Pendant Surface
Surge Protection:	4 kVA	Dimensions:	11.61 in X 7.2 in
Operating Temp:	-22°F to +122°F	Weight:	9 lbs
Rated Life:	134,000 (L70) hours	Warranty:	5 years

Product Options

Mounting	Motion Sensor	Remote Control	Dome Reflector
-----------------	----------------------	-----------------------	-----------------------

Eye Hook Mount
Pendant Mount - Ceiling
Mount

Motion Sensor

No Motion Sensor
Remote Control
Motion Sensor Remote
Control - Qty 1
Motion Sensor Remote
Control - Qty 2
Motion Sensor Remote
Control - Qty 3

Dome Reflector

100 / 120 / 150 / 200 Watt Adjustable UFO Fixture | 14000 to 28000 Lumens



Product Details

SKU: MLLG-LED-HB3-200-50-120-[C]

Web ID: 1952

100 | 120 | 150 | 200 Watts Field Changeable UFO LED fixture produces 14000 | 16800 | 21000 | 28000 lumens (based on your selection) at 140 lumens/watt and replaces 250 | 400 Watt Metal Halide. It is equipped with 1-10V dimmable drivers. White or Black aluminum die-cast heat sink provides optimal heat dissipation. Available in voltage: 100V-277V and Color Temperature: 5000K. Additional options include a motion sensor kit for higher energy savings. Operates in temperatures from -22 F to 122 F.

These high bays comes equipped with a Polycarbonate 120 Glare Resistant lens. Includes built-in 4 kVa surge protection. Mounting options are: Eye-Hook (std) or Pendant. These High Bay Fixtures are IP65 Wet location rated and High Impact IK08 rated.

Field Selectable Power Options (Default is 200 Watts)

100 Watts - 14000 lumens 120 Watts - 16800 lumens 150 Watts - 21000 lumens 200 Watts - 28000 lumens

Motion Sensor Operation: If purchasing a motion sensor please note that a remote control is also required. This will allow you to change the operation of the motion sensor to suit your needs.

Product Specifications

Watts:	100 120 150 200	Dimmable:	1-10V
Lumens:	14000 16800 21000 28000	Beam Angle:	120°
Lumens/Watt:	140	Optics:	Polycarbonate Lens
Replaces:	250 400 Watt Metal Halide	Frequency:	50 / 60 hz
Color Temp:	5000K	Power Factor:	.90
CRI:	80+	THD:	20% Max
IP Rating:	IP65	Housing:	Aluminum Alloy
IK Rating:	IK08	Fixture Color:	Black White
Input Voltage:	100V-277V	Mounting:	Eye-Hook (std) Pendant
Surge Protection:	4kVa line-line, 6kVa line-earth	EPA Rating:	132
Operating Temp:	-22°F to +122°F	Dimensions:	11.02 in X 7.72 in
Rated Life:	170,000 (L70) hours	Weight:	7 lbs
		Warranty:	5 years

Product Options

Mounting Eye Hook Mount Pendant Mount - Ceiling Mount	Motion Sensor Motion Sensor	Remote Control No Motion Sensor Remote Control Motion Sensor Remote Control - Qty 1 Motion Sensor Remote Control - Qty 2 Motion Sensor Remote Control - Qty 3	Dome No Dome Dome
--	---------------------------------------	---	--------------------------------

Product enhancements may result in specification changes without notice. Contact us for the latest information

60 / 80 / 100 Watt Adjustable UFO High Bay | 8400 to 14000 Lumens | 5000K



Product Details

SKU: MLLG-LED-HB3-100-50-120

Web ID: 2024

60 | 80 | 100 Watts Field Changeable UFO LED high bays produces 8400 | 11200 | 14000 lumens (based on your selection) at 140 lumens/watt and replaces 150 | 250 Watt Metal Halide. It is equipped with 1-10V dimmable drivers. Black aluminum die-cast heat sink provides optimal heat dissipation. Available in voltage: 100V-277V and Color Temperature: 5000K. Additional options include a motion sensor kit for higher energy savings. Operates in temperatures from -22 F to 122 F.

It comes equipped with a Polycarbonate 120 lens. Includes built-in 4 kVa surge protection. Mounting options are: Eye-Hook (std) or Pendant. These high bays are IP65 Wet location rated and High Impact IK08 rated.

Field Selectable Power Options (Default is 100 Watts)

60 Watts - 8400 lumens 80 Watts - 11200 lumens 100 Watts - 14000 lumens

Motion Sensor Operation: If purchasing a motion sensor please note that remote control is also required. This will allow you to change the operation of the motion sensor to suit your needs.

Product Specifications

Watts:	60 80 100	Dimmable:	1-10V
Lumens:	8400 11200 14000	Beam Angle:	120°
Lumens/Watt:	140	Optics:	Polycarbonate Lens
Replaces:	150 250 Watt Metal Halide	Frequency:	50 / 60 hz
Color Temp:	5000K	Power Factor:	.90
CRI:	80+	THD:	20% Max
IP Rating:	IP65	Housing:	Aluminum Alloy
IK Rating:	IK08	Fixture Color:	Black
Input Voltage:	100V-277V	Mounting:	Eye-Hook (std) Pendant
Surge Protection:	4kV line-line, 6kV line-earth	EPA Rating:	132
Operating Temp:	-22°F to +122°F	Dimensions:	9.64 in X 7.08 in
Rated Life:	170,000 (L70) hours	Weight:	3.5
		Warranty:	5 years

Product Options

Motion Sensor	Remote Control	Dome	Mounting
Motion Sensor	No Motion Sensor Remote Control Motion Sensor Remote Control - Qty 1 Motion Sensor Remote Control - Qty 2 Motion Sensor Remote Control - Qty 3	No Dome Dome	Eye Hook Pendant Mount

Product enhancements may result in specification changes without notice. Contact us for the latest information