



Commercial Lighting



Industrial Lighting



Sports Lighting

MLLG-LED-HBHO High Bay Product Family



**Why
contractors
choose us**



Free Lighting
Plans to ensure
customer
satisfaction



Dedicated
Lighting
Specialist for
each project



Large
inventory of
LED Lights

Table of Contents

| | Page Number |
|---------------------------|-------------|
| - MLLG-LED-HBHO-100-5-120 | 3 |
| - MLLG-LED-HBHO-150-5-120 | 4 |
| - MLLG-LED-HBHO-240-5-120 | 5 |

100 Watt UFO Light Fixture | 20000 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-LED-HBHO-100-5-120

Web ID: 1526

100 Watt High Efficiency UFO LED high bay produces 20000 lumens at 200 lumens/watt replacing 400 Watt Metal Halide. It is equipped with No dimmable LED driver designed to work with an optional motion sensor. Black aluminum heat sink housing is excellent at dissipating heat. Available in 100V-277V and 4000K or 5000K color temperature.

Other options available: plug-and-play motion sensor kit for more energy savings 120 (std) / 60 90 (opt) anti-glare frosted lens. Includes built-in 4 kVA surge protection. This fixture has different mounting options: Eye-Hook (std) or Pendant or Surface.

These high bays are Wet location IP65 rated and High Impact IK08 rated and can operate in temperatures between -22 F to 122 F

Motion Sensor Operation: If purchasing a motion sensor please note that a remote control is also required. This will allow you to change the operation of the motion sensor to suit your needs.

[Download Motion Sensor Setup Guide](#)

Product Specifications

| | | | |
|--------------------------|---------------------------------|-----------------------|------------------------------------|
| Watts: | 100 | Dimmable: | No |
| Lumens: | 20000 | Beam Angle: | 120° (std) / 60° 90° (opt) |
| Lumens/Watt: | 200 | Frequency: | 50 / 60 hz |
| Replaces: | 400 Watt Metal Halide | Power Factor: | .90 |
| Color Temp: | 4000K 5000K | THD: | 20% Max |
| CRI: | 80+ | Housing: | Die-Cast Aluminum - Epoxy Coating |
| IP Rating: | IP65 | Fixture Color: | Black |
| IK Rating: | IK08 | Mounting: | Eye-Hook (std) Pendant Surface |
| Input Voltage: | 100V-277V | EPA Rating: | 48 |
| Surge Protection: | 4kVa line-line, 6kVa line-earth | Dimensions: | 14.7 in X 7.32 in |
| Operating Temp: | -22°F to +122°F | Weight: | 12 lbs |
| Rated Life: | 134,000 (L70) hours | Warranty: | 5 years |

Product Options

| Lens | Mount | Motion Sensor | Remote Control |
|---|---|---------------|--|
| 120 degree lens 60 degree lens 90 degree lens | Eye Hook Mount Pendant Mount Adjustable Surface Mount | Motion Sensor | No Motion Sensor Remote Control Motion Sensor Remote Control - Qty 1 Motion Sensor Remote Control - Qty 2 Motion Sensor Remote Control - Qty 3 |

150 Watt UFO Light Fixture | 30000 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-LED-HBHO-150-5-120

Web ID: 1527

150 Watt High Efficiency UFO LED high bay produces 30000 lumens at 200 lumens/watt replacing 400 Watt Metal Halide. It is equipped with 1-10V dimmable LED driver designed to work with an optional motion sensor. Black aluminum heat sink housing is excellent at dissipating heat. Available in 100V-277V and 4000K or 5000K color temperature. Our 30000-lumen high bay LED is perfect to replace metal halide lights to create a brighter space and better employee working conditions on the floor. The HBHO-150 high bay light fixture is extremely efficient to help reduce your energy cost while increasing brightness in the facility.

Other options available: plug-and-play motion sensor kit for more energy savings 120 (std) / 60 90 (opt) anti-glare frosted lens. Includes built-in 4 kVa surge protection. This fixture has different mounting options: Eye-Hook (std) or Pendant or Surface.

This high bay is Wet location IP65 rated and High Impact IK08 rated and has an operating temperature range between -22 F to 122 F.

Motion Sensor Operation: If purchasing a motion sensor please note that a remote control is also required. This will allow you to change the operation of the motion sensor to suit your needs.

Product Specifications

[Download Motion Sensor Setup Guide](#)

| | | | |
|--------------------------|---------------------------------|-----------------------|------------------------------------|
| Watts: | 150 | Dimmable: | 1-10V |
| Lumens: | 30000 | Beam Angle: | 120° (std) / 60° 90° (opt) |
| Lumens/Watt: | 200 | Frequency: | 50 / 60 hz |
| Replaces: | 400 Watt Metal Halide | Power Factor: | .90 |
| Color Temp: | 4000K 5000K | THD: | 20% Max |
| CRI: | 80+ | Housing: | Die-Cast Aluminum - Epoxy Coating |
| IP Rating: | IP65 | Fixture Color: | Black |
| IK Rating: | IK08 | Mounting: | Eye-Hook (std) Pendant Surface |
| Input Voltage: | 100V-277V | EPA Rating: | 48 |
| Surge Protection: | 4kVa line-line, 6kVa line-earth | Dimensions: | 14.7 in X 7.32 in |
| Operating Temp: | -22°F to +122°F | Weight: | 12 lbs |
| Rated Life: | 134,000 (L70) hours | Warranty: | 5 years |

Product Options

| Lens | Mount | Motion Sensor | Remote Control |
|---|---|---------------|--|
| 120 degree lens 60 degree lens 90 degree lens | Eye Hook Mount Pendant Mount Adjustable Surface | Motion Sensor | No Motion Sensor Remote Control Motion Sensor Remote Control - Qty 1 Motion Sensor Remote Control - Qty 2 Motion Sensor Remote Control - Qty 3 |

Product enhancements may result in specification changes without notice. Contact us for the latest information

240 Watt UFO High Bay | 45600 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-LED-HBHO-240-5-120

Web ID: 1528

240 Watt High Efficiency UFO LED light produces 45600 lumens at 190 lumens/watt replacing 1000 Watt Metal Halide. It is equipped with 1-10V dimmable LED driver designed to work with an optional motion sensor. Black aluminum heat sink housing is excellent at dissipating heat. Available in 100V-277V and 4000K or 5000K color temperature.

Other options available: plug-and-play motion sensor kit for more energy savings 120 (std) / 60 90 (opt) anti-glare frosted lens. Includes built-in 4 kVa surge protection. This fixture has different mounting options: Eye-Hook (std) or Pendant or Surface.

This high bay is Wet location IP65 rated and High Impact-rated IK08 and can operate in temperatures between -22 F to 122 F

Motion Sensor Operation: If purchasing a motion sensor please note that a remote control is also required. This will allow you to change the operation of the motion sensor to suit your needs.

[Download Motion Sensor Setup Guide](#)

Product Specifications

| | | | |
|--------------------------|---------------------------------|-----------------------|------------------------------------|
| Watts: | 240 | Dimmable: | 1-10V |
| Lumens: | 45600 | Beam Angle: | 120° (std) / 60° 90° (opt) |
| Lumens/Watt: | 190 | Frequency: | 50 / 60 hz |
| Replaces: | 1000 Watt Metal Halide | Power Factor: | .90 |
| Color Temp: | 4000K 5000K | THD: | 20% Max |
| CRI: | 80+ | Housing: | Die-Cast Aluminum - Epoxy Coating |
| IP Rating: | IP65 | Fixture Color: | Black |
| IK Rating: | IK08 | Mounting: | Eye-Hook (std) Pendant Surface |
| Input Voltage: | 100V-277V | EPA Rating: | 48 |
| Surge Protection: | 4kVa line-line, 6kVa line-earth | Dimensions: | 14.7 in X 7.32 in |
| Operating Temp: | -22°F to +122°F | Weight: | 12 lbs |
| Rated Life: | 134,000 (L70) hours | Warranty: | 5 years |

Product Options

| Lens | Mount | Motion Sensor | Remote Control |
|---|---|---------------|--|
| 120 degree lens 60 degree lens 90 degree lens | Eye Hook Mount Pendant Mount Adjustable Surface Mount | Motion Sensor | No Motion Sensor Remote Control Motion Sensor Remote Control - Qty 1 Motion Sensor Remote Control - Qty 2 Motion Sensor Remote Control - Qty 3 |