



Commercial Lighting



Industrial Lighting



Sports Lighting

MLLG-LED-MAR-FLD Marine Light Product Family



**Why
contractors
choose us**



Free Lighting
Plans to ensure
customer
satisfaction



Dedicated
Lighting
Specialist for
each project



Large
inventory of
LED Lights

Table of Contents

	Page Number
- MLLG-LED-MAR-FLD-100-50	3
- MLLG-LED-MAR-FLD-150-50	4
- MLLG-LED-MAR-FLD-200-50	5
- MLLG-LED-MAR-FLD-300-50	6
- MLLG-LED-MAR-FLD-400-50	7
- MLLG-LED-MAR-FLD-540-50	8

100 Watt LED Marine Grade Light | 14000 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-LED-MAR-FLD-100-50

Web ID: 1509

100 Watt marine flood fixture produces 14000 lumens at 140 lumens/watt replacing 400 Watt Metal Halide and is designed to withstand the toughest marine environments with IP68 rated all aluminum fixture with stainless steel screws. They also have an Impact rating of IK10.

This fixture is Corrosion resistant and salt water tested. It comes with a choice of 100V-277V or 277V-480V LED driver. Color temperature options are 3000K or 5000K. The fixture has an adjustable angle trunnion mount and contains all the necessary parts you need to do a quick and easy install. These fixtures can operate in temperatures between -13 F to 131 F.

Product Specifications

Watts:	100	Dimmable:	No
Lumens:	14000	Beam Angle:	90° (std) 25° 40° 60°
Lumens/Watt:	140	Frequency:	50/60 hz
Replaces:	400 Watt Metal Halide	Power Factor:	> .95
Color Temp:	3000K 5000K	THD:	< 15%
CRI:	75+	Housing:	Aircraft Grade Aluminum and Stainless Steel Screws
IP Rating:	IP68	Mounting:	Trunnion
IK Rating:	IK10	Dimensions:	14.56 in X 14.56 in X 4 in
Input Voltage:	100V-277V 277V-480V	Weight:	14.3 lbs
Operating Temp:	-13°F to +131°F	Warranty:	5 years
Rated Life:	80,000 hours		

150 Watt LED Marine Grade Light | 21000 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-LED-MAR-FLD-150-50

Web ID: 2044

150 Watt marine flood fixture produces 21000 lumens at 140 lumens/watt replacing 400 Watt Metal Halide and is designed to withstand the toughest marine environments with IP68 rated all aluminum fixture with stainless steel screws. They also have an Impact rating of IK10.

This fixture is Corrosion resistant and salt water tested. It comes with a choice of 100V-277V or 277V-480V LED driver. Color temperature options are 3000K or 5000K. The fixture has an adjustable angle trunnion mount and contains all the necessary parts you need to do a quick and easy install. These fixtures can operate in temperatures between -13 F to 131 F.

Product Specifications

Watts:	150	Dimmable:	No
Lumens:	21000	Beam Angle:	90° (std) 25° 40° 60°
Lumens/Watt:	140	Frequency:	50/60 hz
Replaces:	400 Watt Metal Halide	Power Factor:	> .95
Color Temp:	3000K 5000K	THD:	< 15%
CRI:	75+	Housing:	Aircraft Grade Aluminum and Stainless Steel Screws
IP Rating:	IP68	Mounting:	Trunnion
IK Rating:	IK10	Dimensions:	16.2 in x 16.2 in x 4 in
Input Voltage:	100V-277V 277V-480V	Weight:	18 lbs
Operating Temp:	-13°F to +131°F	Warranty:	5 years
Rated Life:	80,000 hours		

200 Watt LED Marine Grade Light | 28000 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-LED-MAR-FLD-200-50

Web ID: 1511

200 Watt marine flood fixture produces 28000 lumens at 140 lumens/watt replacing 400 Watt Metal Halide and is designed to withstand the toughest marine environments with IP68 rated all aluminum fixture with stainless steel screws. They also have an Impact rating of IK10.

This fixture is Corrosion resistant and salt water tested. It comes with a choice of 100V-277V or 277V-480V LED driver. Color temperature options are 3000K or 5000K. The fixture has an adjustable angle trunnion mount and contains all the necessary parts you need to do a quick and easy install. These fixtures can operate in temperatures between -13 F to 131 F.

Product Specifications

Watts:	200	Dimmable:	No
Lumens:	28000	Beam Angle:	90° (std) 25° 40° 60°
Lumens/Watt:	140	Frequency:	50/60 hz
Replaces:	400 Watt Metal Halide	Power Factor:	> .95
Color Temp:	3000K 5000K	THD:	< 15%
CRI:	75+	Housing:	Aircraft Grade Aluminum and Stainless Steel Screws
IP Rating:	IP68	Mounting:	Trunnion
IK Rating:	IK10	Dimensions:	18.1 in X 15.75 in X 4 in
Input Voltage:	100V-277V 277V-480V	Weight:	26.4 lbs
Operating Temp:	-13°F to +131°F	Warranty:	5 years
Rated Life:	80,000 hours		

300 Watt LED Marine Grade Light | 42000 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-LED-MAR-FLD-300-50

Web ID: 2045

300 Watt marine flood fixture produces 42000 lumens at 140 lumens/watt replacing 1000 Watt Metal Halide and is designed to withstand the toughest marine environments with IP68 rated all aluminum fixture with stainless steel screws. They also have an Impact rating of IK10.

This fixture is Corrosion resistant and salt water tested. It comes with a choice of 100V-277V or 277V-480V LED driver. Color temperature options are 3000K or 5000K. The fixture has an adjustable angle trunnion mount and contains all the necessary parts you need to do a quick and easy install. These fixtures can operate in temperatures between -13 F to 131 F.

Product Specifications

Watts:	300	Dimmable:	No
Lumens:	42000	Beam Angle:	90° (std) 25° 40° 60°
Lumens/Watt:	140	Frequency:	50/60 hz
Replaces:	1000 Watt Metal Halide	Power Factor:	> .95
Color Temp:	3000K 5000K	THD:	< 15%
CRI:	75+	Housing:	Aircraft Grade Aluminum and Stainless Steel Screws
IP Rating:	IP68	Mounting:	Trunnion
IK Rating:	IK10	Dimensions:	18.1 in X 18.1 in X 4 in
Input Voltage:	100V-277V 277V-480V	Weight:	30 lbs
Operating Temp:	-13°F to +131°F	Warranty:	5 years
Rated Life:	80,000 hours		

400 Watt LED Marine Grade Light | 56000 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-LED-MAR-FLD-400-50

Web ID: 2046

400 Watt marine flood fixture produces 56000 lumens at 140 lumens/watt replacing 1000 Watt Metal Halide and is designed to withstand the toughest marine environments with IP68 rated all aluminum fixture with stainless steel screws. They also have an Impact rating of IK10.

This fixture is Corrosion resistant and salt water tested. It comes with a choice of 100V-277V or 277V-480V LED driver. Color temperature options are 3000K or 5000K. The fixture has an adjustable angle trunnion mount and contains all the necessary parts you need to do a quick and easy install. These fixtures can operate in temperatures between -13 F to 131 F.

Product Specifications

Watts:	400	Dimmable:	No
Lumens:	56000	Beam Angle:	90° (std) 25° 40° 60°
Lumens/Watt:	140	Frequency:	50/60 hz
Replaces:	1000 Watt Metal Halide	Power Factor:	> .95
Color Temp:	3000K 5000K	THD:	< 15%
CRI:	75+	Housing:	Aircraft Grade Aluminum and Stainless Steel Screws
IP Rating:	IP68	Mounting:	Trunnion
IK Rating:	IK10	Dimensions:	25.5 in X 19.5 in X 4 in
Input Voltage:	100V-277V 277V-480V	Weight:	30 lbs
Operating Temp:	-13°F to +131°F	Warranty:	5 years
Rated Life:	80,000 hours		

540 Watt LED Marine Grade Light | 75600 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-LED-MAR-FLD-540-50

Web ID: 1513

540 Watt marine flood fixture produces 75600 lumens at 140 lumens/watt replacing 1500 Watt Metal Halide and is designed to withstand the toughest marine environments with IP68 rated all aluminum fixture with stainless steel screws. They also have an Impact rating of IK10.

This fixture is Corrosion resistant and salt water tested. It comes with a choice of 100V-277V or 277V-480V LED driver. Color temperature options are 3000K or 5000K. The fixture has an adjustable angle trunnion mount and contains all the necessary parts you need to do a quick and easy install. These fixtures can operate in temperatures between -13 F to 131 F.

Product Specifications

Watts:	540	Dimmable:	No
Lumens:	75600	Beam Angle:	90° (std) 25° 40° 60°
Lumens/Watt:	140	Frequency:	50/60 hz
Replaces:	1500 Watt Metal Halide	Power Factor:	> .95
Color Temp:	3000K 5000K	THD:	< 15%
CRI:	75+	Housing:	Aircraft Grade Aluminum and Stainless Steel Screws
IP Rating:	IP68	Mounting:	Trunnion
IK Rating:	IK10	Dimensions:	27.5 in X 21.5 in X 4 in
Input Voltage:	100V-277V 277V-480V	Weight:	51 lbs
Operating Temp:	-13°F to +131°F	Warranty:	5 years
Rated Life:	80,000 hours		