



Commercial Lighting



Industrial Lighting



Sports Lighting

## MLLG-LED-WPFL Wall Pack Product Family



**Why  
contractors  
choose us**



Free Lighting  
Plans to ensure  
customer  
satisfaction



Dedicated  
Lighting  
Specialist for  
each project



Large  
inventory of  
LED Lights

# Table of Contents

	Page Number
- MLLG-LED-WPFL-60-50-PC	3
- MLLG-LED-WPFL-40-50-PC	4
- MLLG-LED-WPFL-80-50-PC	5
- MLLG-LED-WPFL-100-50-PC	6

## 60 Watt LED Wall Pack | 7928 Lumens | 5000K | 100-277V | Forward Throw

### Product Details

**SKU:** MLLG-LED-WPFL-60-50-PC

**Web ID:** 1452

60 Watt flood wall pack produces 7928 lumens at 132 lumens/watt replacing 200 Watt Metal Halide. It has a heavy-duty die-cast aluminum housing and an impact-resistant polycarbonate lens. Excellent impact corrosion and UV resistance with the dark bronze polyester powder finish.

Available in 100V-277V and 5000K Color Temperature. The fixture is bronze in color. The housing has a removable hinge door and multiple entry points - making installation quick and easy. 1/2 in threaded conduit entry with coin plug. They are IP65 UL 1598 wet location rated. Includes Button Photocell.



### Product Specifications

<b>Watts:</b>	60	<b>Dimmable:</b>	No
<b>Lumens:</b>	7928	<b>Beam Angle:</b>	120°
<b>Lumens/Watt:</b>	132	<b>Frequency:</b>	50-60Hz
<b>Replaces:</b>	200 Watt Metal Halide	<b>Power Factor:</b>	> .90
<b>Color Temp:</b>	5000K	<b>THD:</b>	< 20%
<b>CRI:</b>	75+	<b>Housing:</b>	Powder Coated Die-Cast Aluminum with Tempered Glass Lens
<b>IP Rating:</b>	IP65	<b>Fixture Color:</b>	Bronze
<b>Input Voltage:</b>	100V-277V	<b>Mounting:</b>	Wall
<b>Operating Temp:</b>	-40°F to +122°F	<b>Dimensions:</b>	13.1 in L X 9.5 in W X 7.5 in H
<b>Rated Life:</b>	50,000 hours	<b>Warranty:</b>	5 years

## 40 Watt LED Forward Throw Wall Pack | 5300 Lumens | 5000K | 100-277V



### Product Details

**SKU:** MLLG-LED-WPFL-40-50-PC

**Web ID:** 882

40 Watt flood wall pack produces 5300 lumens at 133 lumens/watt replacing 150 Watt Metal Halide. It has a heavy-duty die-cast aluminum housing and an impact-resistant polycarbonate lens. Excellent impact corrosion and UV resistance with the dark bronze polyester powder finish.

Available in 100V-277V and 5000K Color Temperature. The fixture is bronze in color. The housing has a removable hinge door and multiple points of entry - making installation quick and easy. 1/2 in threaded conduit entry with coin plug. They are IP65 UL 1598 wet location rated. Includes Button Photocell.

### Product Specifications

<b>Watts:</b>	40	<b>Dimmable:</b>	0-10V
<b>Lumens:</b>	5300	<b>Beam Angle:</b>	120°
<b>Lumens/Watt:</b>	133	<b>Frequency:</b>	50-60Hz
<b>Replaces:</b>	150 Watt Metal Halide	<b>Power Factor:</b>	> .90
<b>Color Temp:</b>	5000K	<b>THD:</b>	< 20%
<b>CRI:</b>	75+	<b>Housing:</b>	Die cast Aluminum with Bronze Powder Coat Finish
<b>IP Rating:</b>	IP65	<b>Fixture Color:</b>	Bronze
<b>Input Voltage:</b>	100V-277V	<b>Mounting:</b>	Wall
<b>Operating Temp:</b>	-40°F to +122°F	<b>Dimensions:</b>	14.3 in L X 9.1 in W X 7.5 in H
<b>Rated Life:</b>	50,000 hours	<b>Warranty:</b>	5 years

## 80 Watt LED Forward Throw Wall Pack | 11065 Lumens | 5000K | 100-277V



### Product Details

**SKU:** MLLG-LED-WPFL-80-50-PC

**Web ID:** 1453

80 Watt flood wall pack produces 11065 lumens at 138 lumens/watt replacing 250 Watt Metal Halide. It has a heavy-duty die-cast aluminum housing and an impact-resistant polycarbonate lens. Excellent impact corrosion and UV resistance with the dark bronze polyester powder finish.

Available in 100V-277V and 4000K or 5000K Color Temperature. The fixture is bronze in color. The housing has a removable hinge door and multiple entry points - making installation quick and easy. 1/2 in threaded conduit entry with coin plug. They are IP65 UL 1598 wet location rated.

This fixture comes equipped with a built-in button photocell.

### Product Specifications

<b>Watts:</b>	80	<b>Dimmable:</b>	No
<b>Lumens:</b>	11065	<b>Beam Angle:</b>	120°
<b>Lumens/Watt:</b>	138	<b>Frequency:</b>	50-60Hz
<b>Replaces:</b>	250 Watt Metal Halide	<b>Power Factor:</b>	> .90
<b>Color Temp:</b>	4000K   5000K	<b>THD:</b>	< 20%
<b>CRI:</b>	75+	<b>Housing:</b>	Powder Coated Die-Cast Aluminum with Polycarbonate Lens
<b>IP Rating:</b>	IP65	<b>Fixture Color:</b>	Bronze
<b>Input Voltage:</b>	100V-277V	<b>Mounting:</b>	Wall
<b>Operating Temp:</b>	-40°F to +122°F	<b>Dimensions:</b>	13.1 in L X 9.5 in W X 7.5 in H
<b>Rated Life:</b>	50,000 hours	<b>Warranty:</b>	5 years

## 100 Watt LED Wall Pack | 13695 Lumens | 5000K | 100-277V | Forward Throw



### Product Details

**SKU:** MLLG-LED-WPFL-100-50-PC

**Web ID:** 1454

100 Watt flood wall pack produces 13695 lumens at 137 lumens/watt replacing 400 Watt Metal Halide. It has a heavy-duty die-cast aluminum housing and an impact-resistant polycarbonate lens. Excellent impact corrosion and UV resistance with the dark bronze polyester powder finish. Includes a button photocell.

Available in 100V-277V and 5000K Color Temperature. The fixture is bronze in color. The housing has a removable hinge door and multiple points of entry - making installation quick and easy. 1/2 in threaded conduit entry with coin plug. They are IP65 UL 1598 wet location rated.

### Product Specifications

<b>Watts:</b>	100	<b>Dimmable:</b>	No
<b>Lumens:</b>	13695	<b>Beam Angle:</b>	120°
<b>Lumens/Watt:</b>	137	<b>Frequency:</b>	50-60Hz
<b>Replaces:</b>	400 Watt Metal Halide	<b>Power Factor:</b>	> .90
<b>Color Temp:</b>	5000K	<b>THD:</b>	< 20%
<b>CRI:</b>	75+	<b>Housing:</b>	Powder Coated Die-Cast Aluminum with Polycarbonate Lens
<b>IP Rating:</b>	IP65	<b>Fixture Color:</b>	Bronze
<b>Input Voltage:</b>	100V-277V	<b>Mounting:</b>	Wall
<b>Operating Temp:</b>	-40°F to +122°F	<b>Dimensions:</b>	13.1 in L X 9.5 in W X 7.5 in H
<b>Rated Life:</b>	50,000 hours	<b>Warranty:</b>	5 years