



Commercial Lighting



Industrial Lighting



Sports Lighting

MLLG-LN-LED-EXPL Explosion Proof Product Family



**Why
contractors
choose us**



Free Lighting
Plans to ensure
customer
satisfaction



Dedicated
Lighting
Specialist for
each project



Large
inventory of
LED Lights

Table of Contents

	Page Number
- MLLG-LN-LED-EXPL-60-50-120-C1D2	3

60 Watt Explosion Proof Linear LED Light | 7800 Lumens | Class 1 Div 2



Product Details

SKU: MLLG-LN-LED-EXPL-60-50-120-C1D2

Web ID: 1898

Key Features: Wattage: 60 - Lumens: 7800 - Lumens Per Watt: 130 - Replaces: 250 Watt Metal Halide - Voltage: 100V-277V - Expl Rating: Class 1 Division 2 or Class 2 Division 2 - Color Temperature: 5000K - CRI: 70 - Dimming: No - Beam Angles: 120 - Lifespan: 50 000 (L70) hours - Mounting: Bracket or Surface or Wall - Fixture Color: Gray - Frequency: 50-60Hz - Power Factor: .95 - THD: 10%

Durable Construction: Housing: Die-Cast Aluminum - IP Rating: IP66 - Surge Protection: 4kV - Operating Temperature: -40 F to 131 F - Certifications: UL | Rebate Eligible - Warranty: 5 years

Features/Accessories: Explosion Proof C1D2

Measurements: Dimensions: 48.4 in X 4.9 in X 3.5 in - Weight: 17 lbs

Notes: Class 1 Division 2 Group A B C D - Wet Locations (UL 1598)

Product Specifications

Watts:	60	Dimmable:	No
Lumens:	7800	Beam Angle:	120 deg
Lumens/Watt:	130	Frequency:	50-60Hz
Replaces:	250 Watt Metal Halide	Power Factor:	>.95
Color Temp:	5000K	THD:	< 10%
CRI:	70+	Housing:	Die-Cast Aluminum
IP Rating:	IP66	Fixture Color:	Gray
Voltage:	100V-277V	Mount:	Bracket Surface Wall
Surge Protection:	4kV	Dimensions:	48.4 in X 4.9 in X 3.5 in
Operating Temp:	-40 degF to 131 degF	Weight:	17 lbs
Rated Life:	50,000 (L70) hours	Warranty:	5 years