



Commercial Lighting



Industrial Lighting



Sports Lighting

MLLG-LN-LED-PTG Pole Top Lot Light Product Family



**Why
contractors
choose us**



Free Lighting
Plans to ensure
customer
satisfaction



Dedicated
Lighting
Specialist for
each project



Large
inventory of
LED Lights

Table of Contents

	Page Number
- MLLG-LN-LED-PTG-60WC-CC-P	3
- MLLG-LN-LED-PTG-150WC-CC-P	4

20 / 30 / 40 / 60 Watt Adjustable LED Post Top Fixture | 2600 to 7800 Lumens



Product Details

SKU: MLLG-LN-LED-PTG-60WC-CC-P

Web ID: 1556

20 | 30 | 40 | 60 Watt Field Power Adjustable LED post top fixture produces 2600 | 3900 | 5200 | 7800 lumens at 130 LM/W replacing 250 Watt Metal Halide. This LED post-top fixture has an aluminum body/heatsink and a Polycarbonate lens. The fixture is available with Type 5 beam angles and comes in field adjustable 3000K or 4000K or 5000K color temperature.

This post-top fixture is equipped with a 1-10V dimmable driver with 100V-277V voltage. The fixture is BLACK. This fixture easily installs with 3 in Pole adapter on existing poles. Other pole adapter sizes are available on request.

Includes Button Photocell

Product Specifications

Watts:	20 30 40 60	Dimmable:	1-10V
Lumens:	2600 3900 5200 7800	Beam Angle:	Type 5
Lumens/Watt:	130	Optics:	Frosted Tempered Glass
Replaces:	250 Watt Metal Halide	Frequency:	50-60Hz
Color Temp:	3000K 4000K 5000K	Power Factor:	> .90
CRI:	80+	THD:	< 20%
IP Rating:	IP65	Housing:	Die-Cast Aluminum
Input Voltage:	100V-277V	Fixture Color:	Black
Operating Temp:	-22°F to +140°F	Mounting:	3 in Pole
Rated Life:	50,000 (L70) hours	EPA Rating:	1.75
		Dimensions:	25.6 in H X 17 in D
		Warranty:	5 years

80 / 100 / 120 /150 Watt Adjustable LED Post Top Fixture



Product Details

SKU: MLLG-LN-LED-PTG-150WC-CC-P

Web ID: 1558

80 | 100 | 120 | 150 Watt LED post top fixture produces 10400 | 13000 | 15600 | 19500 lumens at 130 LM/W replacing 400 Watt Metal Halide. This post-top fixture has an aluminum body/heatsink and a Polycarbonate lens. The fixture is available with 90 X 140 beam angles. You can select the Color Temperature with a toggle switch: 3000K or 4000K or 5000K.

This LED post-top fixture is equipped with a 1-10V dimmable driver with 100V-277V voltage. The fixture is BLACK. This fixture easily installs with 3 in Pole adapter on existing poles. Other pole adapter sizes are available on request.

Includes Button Photocell

Product Specifications

Watts:	80 100 120 150	Dimmable:	1-10V
Lumens:	10400 13000 15600 19500	Beam Angle:	90 X 140
Lumens/Watt:	130	Optics:	Frosted Tempered Glass
Replaces:	400 Watt Metal Halide	Frequency:	50-60Hz
Color Temp:	3000K 4000K 5000K	Power Factor:	> .90
CRI:	80+	THD:	< 20%
IP Rating:	IP65	Housing:	Die-Cast Aluminum
Input Voltage:	100V-277V	Fixture Color:	Black
Operating Temp:	-22°F to +140°F	Mounting:	3 in Pole
Rated Life:	50,000 (L70) hours	EPA Rating:	1.75
		Dimensions:	25.6 in H X 17 in D
		Warranty:	5 years