



Commercial Lighting



Industrial Lighting



Sports Lighting

## MLLG-LN-LED-WPFL Wall Pack Product Family



**Why  
contractors  
choose us**



Free Lighting  
Plans to ensure  
customer  
satisfaction



Dedicated  
Lighting  
Specialist for  
each project



Large  
inventory of  
LED Lights

# Table of Contents

	Page Number
- MLLG-LN-LED-WPFL-120-50-PC	3
- MLLG-LN-LED-WPFL-120-CC-PC	4
- MLLG-LN-LED-WPFL-150-50-PC	5

## 120 Watt LED Forward Throw Wall Pack | 15000 Lumens | 5000K | 100-277V



### Product Details

**SKU:** MLLG-LN-LED-WPFL-120-50-PC

**Web ID:** 1564

120 Watt flood wall pack produces 15000 lumens at 125 lumens/watt replacing 400 Watt Metal Halide. It has a heavy-duty die-cast aluminum housing and an impact-resistant polycarbonate 120 lens. This fixture is designed for outdoor locations with excellent impact corrosion and UV resistance. Available in 100V-277V and 5000K Color Temperature. The fixture comes in a dark bronze polyester powder finish.

This fixture comes equipped with a built-in button photocell. This fixture comes with the Wall mount. The housing has a removable hinge door and multiple points of entry. 1/2 in threaded conduit entry with coin plug. They are IP65 UL 1598 wet location rated.

### Product Specifications

<b>Watts:</b>	120	<b>Dimmable:</b>	1-10V
<b>Lumens:</b>	15000	<b>Beam Angle:</b>	120°
<b>Lumens/Watt:</b>	125	<b>Frequency:</b>	50-60Hz
<b>Replaces:</b>	400 Watt Metal Halide	<b>Power Factor:</b>	> .90
<b>Color Temp:</b>	5000K	<b>THD:</b>	< 20%
<b>CRI:</b>	70+	<b>Housing:</b>	Powder Coated Die-Cast Aluminum with Polycarbonate Lens
<b>IP Rating:</b>	IP65	<b>Fixture Color:</b>	Bronze
<b>Input Voltage:</b>	100V-277V	<b>Mounting:</b>	Wall
<b>Operating Temp:</b>	-40°F to +122°F	<b>Dimensions:</b>	18.3 in L X 9.3 in W X 9 in D
<b>Rated Life:</b>	50,000 hours	<b>Warranty:</b>	5 years

## 60 / 80 / 100 / 120 Watt LED Forward Throw Wall Pack | 7800 to 15600 Lumens



### Product Details

**SKU:** MLLG-LN-LED-WPFL-120-CC-PC

**Web ID:** 2131

60 | 80 | 100 | 120 Wattage adjustable flood wall pack produces 7800 | 10400 | 13000 | 15600 lumens at 130 lumens/watt replacing 250 | 400 Watt Metal Halide. It has a heavy-duty die-cast aluminum housing and an impact-resistant glass lens. This fixture is designed for outdoor locations with excellent impact corrosion and UV resistance. Available in 100V-277V and 3000K or 4000K or 5000K Color Adjustable Temperature. The fixture comes in a dark bronze powder coat finish color.

This fixture comes equipped with a built-in button photocell. This fixture comes with the Wall mount. They are IP65 UL 1598 wet location rated.

### Product Specifications

<b>Watts:</b>	60   80   100   120	<b>Dimmable:</b>	No
<b>Lumens:</b>	7800   10400   13000   15600	<b>Beam Angle:</b>	120°
<b>Lumens/Watt:</b>	130	<b>Optics:</b>	Glass Lens
<b>Replaces:</b>	250   400 Watt Metal Halide	<b>Frequency:</b>	50-60Hz
<b>Color Temp:</b>	3000K   4000K   5000K	<b>Power Factor:</b>	> .90
<b>CRI:</b>	70+	<b>THD:</b>	< 20%
<b>IP Rating:</b>	IP65	<b>Housing:</b>	Powder Coated Die-Cast Aluminum
<b>Input Voltage:</b>	100V-277V	<b>Fixture Color:</b>	Bronze
<b>Operating Temp:</b>	-4°F to +113°F	<b>Mounting:</b>	Wall
<b>Rated Life:</b>	50,000 hours	<b>Dimensions:</b>	14.2 in L X 7.4 in W X 9.2 in H
		<b>Weight:</b>	8 lbs
		<b>Warranty:</b>	5 years

## 150 Watt LED Wall Pack | 19500 Lumens | 5000K | 100-277V | Photocell



### Product Details

**SKU:** MLLG-LN-LED-WPFL-150-50-PC

**Web ID:** 1565

150 Watt flood wall pack produces 19500 lumens at 130 lumens/watt replacing 400 Watt Metal Halide. It has a heavy-duty die-cast aluminum housing and an impact-resistant polycarbonate 120 lens. This fixture is designed for outdoor locations with excellent impact corrosion and UV resistance. Available in 100V-277V and 5000K Color Temperature. The fixture comes in a dark bronze polyester powder finish in color and has a Polycarbonate Optical 120 Lens.

This fixture comes equipped with a built-in button photocell. This fixture comes with the Wall mount. The housing has a removable hinge door and multiple points of entry. 1/2 in threaded conduit entry with coin plug. They are IP65 UL 1598 wet location rated.

### Product Specifications

<b>Watts:</b>	150	<b>Dimmable:</b>	1-10V
<b>Lumens:</b>	19500	<b>Beam Angle:</b>	120°
<b>Lumens/Watt:</b>	130	<b>Frequency:</b>	50-60Hz
<b>Replaces:</b>	400 Watt Metal Halide	<b>Power Factor:</b>	> .90
<b>Color Temp:</b>	5000K	<b>THD:</b>	< 20%
<b>CRI:</b>	70+	<b>Housing:</b>	Powder Coated Die-Cast Aluminum with Polycarbonate Lens
<b>IP Rating:</b>	IP65	<b>Fixture Color:</b>	Bronze
<b>Input Voltage:</b>	100V-277V	<b>Mounting:</b>	Wall
<b>Operating Temp:</b>	-40°F to +122°F	<b>Dimensions:</b>	18.3 in L X 9.3 in W X 9 in D
<b>Rated Life:</b>	50,000 hours	<b>Warranty:</b>	5 years