


Commercial Lighting

Industrial Lighting

Sports Lighting

MLLG-LN-LED LED Exit Product Family





Why contractors choose us

Free Lighting
Plans to ensure
customer
satisfaction

Dedicated Lighting Specialist for each project Large inventory of LED Lights

Table of Contents

Page Number
3
4
5
6
7
8



2 Watt LED Exit Sign | 90 Minute Battery Backup | Wet Location Rated



Product Details

SKU: LLS-WD-EXIT-RG-IP65 **Web ID:** 2209

LED Emergency Exit Sign with 90 Min Emergency Backup 100V-277V 32 F to 104 F operating temperatures IP65 Rated fire-resistant. Customizable parts included for either red or green lettering with or without arrows. 2 Year Warranty.

Watts:	2	Frequency:	50-60Hz
Housing:	Injection-molded, flame-retardant, high impact thermoplastic	Fixture Color:	White
IP Rating:	IP65	Lettering:	Red or Green With or Without Arrows
Mounting:	Surface Mount	Operating Temp:	32°F to +104°F
Dimensions:	12.5 in L X 2.5 in W X 8 in H	Rated Life:	50,000 hours
Input Voltage:	120-277V	Warranty:	2 years



3 Watt LED Exit Sign | 90 Minute Battery Backup



Product Details

SKU: MLLG-LN-LED-EXIT1 **Web ID:** 1551

Bright and efficient 3 Watts Emergency Exit Light with 6 in Red LED letters. Voltage input is 100V-277V. Housing is Injection-molded thermoplastic ABS housing. Charging time is 24 hours and battery discharge time is 90 minutes.

The LED series is ETL listed and meets or exceeds the following: UL 94V-0 Flame resistant and fire rating.

Watts:	3	Fixture Color:	White
Housing:	Injection-Molded Thermoplastic ABS	Lettering:	Red
Mounting:	Surface	Operating Temp:	32°F to +104°F
Dimensions:	12 in L X 7.5 in H X 4.33 in D	Rated Life:	50,000 hours
Input Voltage:	100-277V	Warranty:	3 years
Frequency:	50-60Hz		



5 Watt LED Exit Sign | 90 Minute Battery Backup



Product Details

discharge time is 90 minutes.

SKU: MLLG-WD-LED-EXIT1 **Web ID:** 2070

Bright and efficient 5 Watts Emergency Exit LED Light with 6 inch Red LED letters. Voltage input is 100V-277V. Housing is Injection-molded thermoplastic ABS housing. Charging time is 24 hours and battery

The LED series is ETL listed and meets or exceeds the following: UL 94V-0 Flame resistance and fire rating.

Watts:	5	Fixture Color:	White
Housing:	Injection-Molded Thermoplastic ABS	Lettering:	Red
Mounting:	Surface	Operating Temp:	32°F to +104°F
Dimensions:	12 in L X 7.5 in H X 4.33 in D	Rated Life:	50,000 hours
Input Voltage:	100-277V	Warranty:	2 years
Frequency:	50-60Hz		



2.4 Watt LED Emergency Light and Exit Sign | 90 Minute Battery Backup



Product Details

SKU: MLLG-LN-LED-EXIT2-2L **Web ID:** 1613

This Emergency Exit LED Light is the most economical LED Combo (including LED emergency light heads) for general purpose applications. The injection molded thermoplastic material resists discoloration due to UV radiation and the energy-efficient low-maintenance LEDs provide bright illumination. The unit has universal mounting capability.

Watts:	3	Frequency:	50-60Hz
Replaces:	36W CFL	Fixture Color:	White
Housing:	Injection-Molded Thermoplastic ABS	Lettering:	Red
Mounting:	Surface	Operating Temp:	32°F to +104°F
Dimensions:	12 in L X 7.5 in H X 4.33 in D	Rated Life:	50,000 hours
Input Voltage:	100-277V	Warranty:	3 years



2 Watt LED Emergency Light | 90 Minute Battery Backup



Product Details

SKU: MLLG-LN-LED-EML-2 Web ID: 1552

2 Watt Emergency Exit Light produces 150 lumens for up to 90 minutes. LED heads are adjustable so you can aim and point for optimal light distribution.

Watts:	2	Frequency:	50-60Hz
Lumens:	150	Fixture Color:	White
Housing:	Injection-Molded Thermoplastic ABS	Operating Temp:	32°F to +104°F
Mounting:	Surface	Rated Life:	50,000 hours
Dimensions:	12 in L X 7.5 in H X 4.33 in D	Warranty:	3 years
Input Voltage:	100-277V		



4 Watt LED Emergency Light | 90 Minute Battery Backup



Product Details

SKU: MLLG-WD-LED-EML-2 Web ID: 2053

4 Watt Emergency Exit LED Light produces 300 lumens for up to 90 minutes. LED heads are adjustable so you can aim and point for optimal light distribution.

		T.	
Watts:	4	Input Voltage:	100-277V
Lumens:	300	Frequency:	50-60Hz
Housing:	Injection-Molded Thermoplastic ABS	Fixture Color:	White
Mounting:	Surface	Operating Temp:	32°F to +104°F
Dimensions:	12 in L X 7.5 in H X 4.33 in D	Rated Life:	50,000 hours
Weight:	19.6 lbs	Warranty:	3 years