



Commercial Lighting



Industrial Lighting



Sports Lighting

MLLG-LS-LED-FLD Flood Light Product Family



**Why
contractors
choose us**



Free Lighting
Plans to ensure
customer
satisfaction



Dedicated
Lighting
Specialist for
each project



Large
inventory of
LED Lights

Table of Contents

	Page Number
- MLLG-LED-FLD4-150-CC	3
- MLLG-LS-LED-FLD2-35-CC-KM	4
- MLLG-LS-LED-FLD2-35-CC-YM	5
- MLLG-LS-LED-FLD2-80-CC-KM	6
- MLLG-LS-LED-FLD2-80-CC-YM	7
- MLLG-LS-LED-FLD2-150-CC-SF	8
- MLLG-LS-LED-FLD2-150-CC-YM	9
- MLLG-LS-LED-FLD-150-5	10
- MLLG-LS-LED-FLD-200-5	11
- MLLG-YA-LED-FLD-50-5-KM	12
- MLLG-YA-LED-FLD-50-5-YM	13
- MLLG-WD-LED-FLDT-45-5-KM	14

38 / 75 / 112 / 150 Watt Adjustable LED Flood Light | 5700 to 22500 Lumens



Product Details

SKU: MLLG-LED-FLD4-150-CC

Web ID: 1951

38 | 75 | 112 | 150 Watt Changeable Color Changeable Yoke or Slipfitter Mount flood light replaces 250 | 400 Watt Metal Halide and produces 5700 | 11250 | 16800 | 22500 lumens at 159 lumens/watt. The heavy-duty die-cast aluminum frame is anti-corrosion powder coated for years of maintenance-free lighting. Color Temperature choice is 3000K or 4000K or 5000K.

Flood Light is equipped with a No dimmable 100V-277V LED Driver. This flood light fixture is IP66 rated for wet locations and can operate in temperatures ranging from -22 F to 113 F. It is High Impact IK08 Rated

Product Specifications

Watts:	38 75 112 150	Dimmable:	No
Lumens:	5700 11250 16800 22500	Beam Angle:	PC Lens 65x95 Degree Optic
Lumens/Watt:	159	Optics:	Polycarbonate Lens
Replaces:	250 400 Watt Metal Halide	Frequency:	50-60Hz
Color Temp:	3000K 4000K 5000K	Power Factor:	.9
CRI:	70+	THD:	15%
IP Rating:	IP66	Housing:	Powder Coated Aluminum
IK Rating:	IK08	Fixture Color:	Bronze
Input Voltage:	100V-277V	Mounting:	Yoke Slip Fitter
Surge Protection:	10KV	EPA Rating:	0.64
Operating Temp:	-22°F to +113°F	Dimensions:	11.8 in L X 12 in W X 10 in D
Rated Life:	50,000 (L70) hours	Weight:	7.48 lbs
		Warranty:	5 years

Product Options

Mount

Trunnion - Wall Bracket
Slip fitter

15 / 25 / 35 Watt Adjustable LED Flood Light | 2025 to 4700 Lumens



Product Details

SKU: MLLG-LS-LED-FLD2-35-CC-KM

Web ID: 2028

15 | 25 | 35 Power Selectable Knuckle Mount flood light replaces 100 Watt Metal Halide and produces 2025 | 2700 | 4700 lumens at 135 lumens/watt. The heavy-duty die-cast aluminum frame is anti-corrosion powder coated for years of maintenance-free lighting.

Flood Light can be equipped with a No dimmable 100V-277V LED Driver. You can select one of the following color temperatures: 3000K or 4000K or 5000K. This fixture is IP65 rated for wet locations and can operate in temperatures ranging from -4 F to 140 F.

Product Specifications

Watts:	15 25 35	Dimmable:	No
Lumens:	2025 2700 4700	Optics:	Tempered Glass Lens
Lumens/Watt:	135	Frequency:	50-60Hz
Replaces:	100 Watt Metal Halide	Power Factor:	.9
Color Temp:	3000K 4000K 5000K	THD:	15%
CRI:	70+	Housing:	Powder Coated Aluminum
IP Rating:	IP65	Fixture Color:	Bronze
Input Voltage:	100V-277V	Mounting:	Knuckle
Operating Temp:	-4°F to +140°F	Dimensions:	9.8 in L X 6.9 in W
Rated Life:	50,000 (L70) hours	Weight:	5 lbs
		Warranty:	5 years

15 / 25 / 35 Watt Adjustable LED Flood Light | 2025 to 4700 Lumens



Product Details

SKU: MLLG-LS-LED-FLD2-35-CC-YM

Web ID: 2029

15 | 25 | 35 Power Selectable Yoke Mount flood light replaces 100 Watt Metal Halide and produces 2025 | 2700 | 4700 lumens at 135 lumens/watt. The heavy-duty die-cast aluminum frame is anti-corrosion powder coated for years of maintenance-free lighting.

Flood Light can be equipped with a No dimmable 100V-277V LED Driver. You can select one of the following color temperatures: 3000K or 4000K or 5000K. This fixture is IP65 rated for wet locations and can operate in temperatures ranging from -4 F to 140 F.

Product Specifications

Watts:	15 25 35	Dimmable:	No
Lumens:	2025 2700 4700	Optics:	Tempered Glass Lens
Lumens/Watt:	135	Frequency:	50-60Hz
Replaces:	100 Watt Metal Halide	Power Factor:	.9
Color Temp:	3000K 4000K 5000K	THD:	15%
CRI:	70+	Housing:	Powder Coated Aluminum
IP Rating:	IP65	Fixture Color:	Bronze
Input Voltage:	100V-277V	Mounting:	Yoke
Operating Temp:	-4°F to +140°F	Dimensions:	9.8 in L X 6.9 in W
Rated Life:	50,000 (L70) hours	Weight:	5 lbs
		Warranty:	5 years

35 / 60 / 80 Watt Adjustable LED Flood Light | 4050 to 10800 Lumens



Product Details

SKU: MLLG-LS-LED-FLD2-80-CC-KM

Web ID: 2030

35 | 60 | 80 Power Selectable Knuckle Mount flood light replaces 250 Watt Metal Halide and produces 4050 | 8100 | 10800 lumens at 135 lumens/watt. The heavy-duty die-cast aluminum frame is anti-corrosion powder coated for years of maintenance-free lighting.

Flood Light can be equipped with a No dimmable 100V-277V LED Driver. You can select one of the following color temperatures: 3000K or 4000K or 5000K. This fixture is IP65 rated for wet locations and can operate in temperatures ranging from -4 F to 140 F.

Product Specifications

Watts:	35 60 80	Dimmable:	No
Lumens:	4050 8100 10800	Optics:	Tempered Glass Lens
Lumens/Watt:	135	Frequency:	50-60Hz
Replaces:	250 Watt Metal Halide	Power Factor:	.9
Color Temp:	3000K 4000K 5000K	THD:	15%
CRI:	70+	Housing:	Powder Coated Aluminum
IP Rating:	IP65	Fixture Color:	Bronze
Input Voltage:	100V-277V	Mounting:	Knuckle
Operating Temp:	-4°F to +140°F	Dimensions:	10.5 in L X 9.85 in W
Rated Life:	50,000 (L70) hours	Weight:	8 lbs
		Warranty:	5 years

35 / 60 / 80 Watt Adjustable LED Flood Light | 4050 to 10800 Lumens



Product Details

SKU: MLLG-LS-LED-FLD2-80-CC-YM

Web ID: 2031

35 | 60 | 80 Power Selectable Yoke Mount flood light replaces 250 Watt Metal Halide and produces 4050 | 8100 | 10800 lumens at 135 lumens/watt. The heavy-duty die-cast aluminum frame is anti-corrosion powder coated for years of maintenance-free lighting.

Flood Light can be equipped with a No dimmable 100V-277V LED Driver. You can select one of the following color temperatures: 3000K or 4000K or 5000K. This fixture is IP65 rated for wet locations and can operate in temperatures ranging from -4 F to 140 F.

Product Specifications

Watts:	35 60 80	Dimmable:	No
Lumens:	4050 8100 10800	Optics:	Tempered Glass Lens
Lumens/Watt:	135	Frequency:	50-60Hz
Replaces:	250 Watt Metal Halide	Power Factor:	.9
Color Temp:	3000K 4000K 5000K	THD:	15%
CRI:	70+	Housing:	Powder Coated Aluminum
IP Rating:	IP65	Fixture Color:	Bronze
Input Voltage:	100V-277V	Mounting:	Yoke
Operating Temp:	-4°F to +140°F	Dimensions:	10.5 in L X 9.85 in W
Rated Life:	50,000 (L70) hours	Weight:	8 lbs
		Warranty:	5 years

100 / 120 / 150 Watt Adjustable LED Flood Light | 10800 to 20250 Lumens



Product Details

SKU: MLLG-LS-LED-FLD2-150-CC-SF

Web ID: 2032

100 | 120 | 150 Power Selectable Slipfitter Mount flood light replaces 400 Watt Metal Halide and produces 10800 | 13500 | 20250 lumens at 135 lumens/watt. The heavy-duty die-cast aluminum frame is anti-corrosion powder coated for years of maintenance-free lighting.

Flood Light can be equipped with a No dimmable 100V-277V LED Driver. You can select one of the following color temperatures: 3000K or 4000K or 5000K. This fixture is IP65 rated for wet locations and can operate in temperatures ranging from -4 F to 140 F.

Product Specifications

Watts:	100 120 150	Dimmable:	No
Lumens:	10800 13500 20250	Optics:	Tempered Glass Lens
Lumens/Watt:	135	Frequency:	50-60Hz
Replaces:	400 Watt Metal Halide	Power Factor:	.9
Color Temp:	3000K 4000K 5000K	THD:	15%
CRI:	70+	Housing:	Powder Coated Aluminum
IP Rating:	IP65	Fixture Color:	Bronze
Input Voltage:	100V-277V	Mounting:	Slip Fitter
Operating Temp:	-4°F to +140°F	Dimensions:	11.55 in L X 12.09 in W
Rated Life:	50,000 (L70) hours	Weight:	15 lbs
		Warranty:	5 years

100 to 150 Watt Power Adjustable LED Flood Light | 10800 to 20250 Lumens



Product Details

SKU: MLLG-LS-LED-FLD2-150-CC-YM

Web ID: 2033

100 | 120 | 150 Power Selectable Yoke Mount flood light replaces 400 Watt Metal Halide and produces 10800 | 13500 | 20250 lumens at 135 lumens/watt. The heavy-duty die-cast aluminum frame is anti-corrosion powder coated for years of maintenance-free lighting.

Flood Light can be equipped with a No dimmable 100V-277V LED Driver. You can select one of the following color temperatures: 3000K or 4000K or 5000K. This fixture is IP65 rated for wet locations and can operate in temperatures ranging from -4 F to 140 F.

Product Specifications

Watts:	100 120 150	Dimmable:	No
Lumens:	10800 13500 20250	Optics:	Tempered Glass Lens
Lumens/Watt:	135	Frequency:	50-60Hz
Replaces:	400 Watt Metal Halide	Power Factor:	.9
Color Temp:	3000K 4000K 5000K	THD:	15%
CRI:	70+	Housing:	Powder Coated Aluminum
IP Rating:	IP65	Fixture Color:	Bronze
Input Voltage:	100V-277V	Mounting:	Yoke
Operating Temp:	-4°F to +140°F	Dimensions:	11.55 in L X 12.09 in W
Rated Life:	50,000 (L70) hours	Weight:	15 lbs
		Warranty:	5 years

150w LED Flood Light | 19500 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-LS-LED-FLD-150-5

Web ID: 1758

150 Watt Trunnion Mount flood light produces 19500 lumens at 130 lumens/watt replacing 400 Watt Metal Halide. The heavy-duty aluminum frame is UV-resistant and powder coated for years of minimal maintenance. Flood Light can be equipped with a No dimmable driver.

It comes in 100V-277V LED Driver and is available in 5000K color temperature. The standard beam angle is 120°. This fixture is Wet location IP65 rated and can operate in temperatures ranging from -31 F to 131 F.

Product Specifications

Watts:	150	Dimmable:	No
Lumens:	19500	Beam Angle:	120°
Lumens/Watt:	130	Optics:	Tempered Glass Lens
Replaces:	400 Watt Metal Halide	Frequency:	50/60 hz
Color Temp:	5000K	THD:	< 15%
CRI:	70+	Housing:	Powder Coated Aluminum
IP Rating:	IP65	Fixture Color:	Bronze
Input Voltage:	100V-277V	Mounting:	Trunnion
Operating Temp:	-31°F to +131°F	Dimensions:	12.9 in X 13.3 in X 5.5 in
Rated Life:	50,000 hours	Weight:	17 lbs
		Warranty:	5 years

200 Watt LED Area Flood Light | 26000 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-LS-LED-FLD-200-5

Web ID: 1759

200 Watt Trunnion Mount flood light produces 26000 lumens at 130 lumens/watt replacing 400 Watt Metal Halide. The heavy-duty aluminum frame is UV resistant and powder coated for years of minimal maintenance. Flood Light can be equipped with a No dimmable driver.

It comes in 100V-277V LED Driver and is available in 5000K color temperature. The standard beam angle is 120°. This fixture is Wet location IP65 rated and can operate in temperatures ranging from -31 F to 131 F.

Product Specifications

Watts:	200	Dimmable:	No
Lumens:	26000	Beam Angle:	120°
Lumens/Watt:	130	Optics:	Tempered Glass Lens
Replaces:	400 Watt Metal Halide	Frequency:	50/60 hz
Color Temp:	5000K	THD:	< 15%
CRI:	70+	Housing:	Powder Coated Aluminum
IP Rating:	IP65	Fixture Color:	Bronze
Input Voltage:	100V-277V	Mounting:	Trunnion
Operating Temp:	-31°F to +131°F	Dimensions:	14.2 in X 15.7 in X 5.5 in
Rated Life:	50,000 hours	Weight:	21 lbs
		Warranty:	5 years

50 Watt LED Flood Light | 6500 Lumens | 5000K | 100-277V | Knuckle Mount



Product Details

SKU: MLLG-YA-LED-FLD-50-5-KM

Web ID: 1959

50 Watt Knuckle Mount Flood Light replaces 150 Watt Metal Halide and produces 6500 lumens at 130 lumens/watt. The heavy-duty die-cast aluminum frame is anti-corrosion powder coated for years of maintenance-free lighting. Color Temperature is: 5000K.

Flood Light can be equipped with a No dimmable 100V-277V LED Driver. This flood light is IP65 rated for wet locations and can operate in temperatures ranging from -40 F to 113 F.

Product Specifications

Watts:	50	Dimmable:	No
Lumens:	6500	Optics:	Polycarbonate Lens
Lumens/Watt:	130	Frequency:	50-60Hz
Replaces:	150 Watt Metal Halide	Power Factor:	.9
Color Temp:	5000K	THD:	15%
CRI:	80+	Housing:	Powder Coated Aluminum
IP Rating:	IP65	Fixture Color:	Bronze
Input Voltage:	100V-277V	Mounting:	1/2 in NPT Knuckle
Operating Temp:	-40°F to +113°F	Dimensions:	10.91 in L X 8.27 in W
Rated Life:	50,000 (L70) hours	Weight:	3.1 lbs
		Warranty:	5 years

30 / 40 / 50 Watt Adjustable LED Flood Light | 3900 to 6500 Lumens | 5000K



Product Details

SKU: MLLG-YA-LED-FLD-50-5-YM

Web ID: 1615

30 | 40 | 50 Watt Changeable Yoke Mount Flood Light replaces 100 | 150 Watt Metal Halide and produces 3900 | 5200 | 6500 lumens at 130 lumens/watt. The heavy-duty die-cast aluminum frame is anti-corrosion powder coated for years of maintenance-free lighting. Color Temperature is 5000K.

Flood Light can be equipped with a No dimmable 100V-277V LED Driver. This flood light fixture is IP65 rated for wet locations and can operate in temperatures ranging from -40 F to 113 F.

Product Specifications

Watts:	30 40 50	Dimmable:	No
Lumens:	3900 5200 6500	Optics:	Polycarbonate Lens
Lumens/Watt:	130	Frequency:	50-60Hz
Replaces:	100 150 Watt Metal Halide	Power Factor:	.9
Color Temp:	5000K	THD:	15%
CRI:	80+	Housing:	Powder Coated Aluminum
IP Rating:	IP65	Fixture Color:	Bronze
Input Voltage:	100V-277V	Mounting:	Yoke
Operating Temp:	-40°F to +113°F	Dimensions:	8.86 in L X 8.27 in W
Rated Life:	50,000 (L70) hours	Weight:	3.1 lbs
		Warranty:	5 years

45 Watt LED Flood Light | 6750 Lumens | 5000K | 100-277V | Built In Photocell



Product Details

SKU: MLLG-WD-LED-FLDT-45-5-KM

Web ID: 1925

45 Watts Knuckle Mount flood light replaces 150 Watt Metal Halide and produces 6750 lumens at 150 lumens/watt. The heavy-duty die-cast bronze aluminum frame is anti-corrosion powder coated for years of maintenance-free lighting. Comes with an 18 in cord. Units come standard with Button Photocell.

Flood Light can be equipped with a 1-10V dimmable 100V-277V LED Driver. Color temperature is 5000K. This fixture is IP65 rated for wet locations and can operate in temperatures ranging from -22 F to 113 F.

Product Specifications

Watts:	45	Dimmable:	1-10V
Lumens:	6750	Beam Angle:	100°
Lumens/Watt:	150	Optics:	Polycarbonate Lens
Replaces:	150 Watt Metal Halide	Frequency:	50-60Hz
Color Temp:	5000K	Power Factor:	.95
CRI:	70+	THD:	15%
IP Rating:	IP65	Housing:	Powder Coated Aluminum
Input Voltage:	100V-277V	Fixture Color:	Bronze
Operating Temp:	-22°F to +113°F	Mounting:	1/2 in NPT Knuckle
Rated Life:	50,000 (L70) hours	Dimensions:	8.75 in L X 8.26 in W X 4.76 in D
		Weight:	4.2 lbs
		Warranty:	5 years