



Commercial Lighting



Industrial Lighting



Sports Lighting

## MLLG-YA-LED-PTD Pole Top Lot Light Product Family



**Why  
contractors  
choose us**



Free Lighting  
Plans to ensure  
customer  
satisfaction



Dedicated  
Lighting  
Specialist for  
each project



Large  
inventory of  
LED Lights

# Table of Contents

	Page Number
- MLLG-YA-LED-PTD-30	3
- MLLG-YA-LED-PTD-60	4
- MLLG-YA-LED-PTD-100-CC	5
- MLLG-YA-LED-PTD-120-CC	6

## 30 Watt LED Decorative Post Top Fixture | 3610 Lumens



### Product Details

**SKU:** MLLG-YA-LED-PTD-30

**Web ID:** 1202

30 Watt Decorative LED post top fixture produces 3610 lumens at 120 LM/W replacing 100 Watt Metal Halide. The fixture has a 360 degree beam angle. Photocell is optional. The fixture is Black. Color is adjustable with onboard toggle: 3000K or 4000K or 5000K.

Fixtures is equipped with a 100V-277V voltage LED Driver. It can dim as well: 1-10V. This fixture includes a slipfitter bracket that can be mounted on a 3 pole. It is rated for Wet locations and is IP65 rated. They can operate in temperatures ranging -40 F to 113 F.

### Product Specifications

<b>Watts:</b>	30	<b>Dimmable:</b>	1-10V
<b>Lumens:</b>	3610	<b>Beam Angle:</b>	Type 5
<b>Lumens/Watt:</b>	120	<b>Optics:</b>	Frosted Tempered Glass
<b>Replaces:</b>	100 Watt Metal Halide	<b>Frequency:</b>	50-60Hz
<b>Color Temp:</b>	3000K   4000K   5000K	<b>Power Factor:</b>	> .90
<b>CRI:</b>	70+	<b>THD:</b>	< 20%
<b>IP Rating:</b>	IP65	<b>Housing:</b>	Die-Cast Aluminum
<b>Input Voltage:</b>	100V-277V	<b>Mounting:</b>	3 in Pole
<b>Operating Temp:</b>	-40°F to +113°F	<b>EPA Rating:</b>	1.2
<b>Rated Life:</b>	50,000 (L70) hours	<b>Dimensions:</b>	11.9 in X 11.9 in X 26 in
		<b>Warranty:</b>	5 years

## 30/50/60 Watt Adjustable LED Decorative Post Top Fixture | 3600 to 7200 Lumens



### Product Details

**SKU:** MLLG-YA-LED-PTD-60

**Web ID:** 1433

30 | 50 | 60 Watt Changing Decorative LED post top fixture produces 3600 | 6000 | 7200 lumens at 120 LM/W replacing 250 Watt Metal Halide. The fixture has a 360 degree beam angle. Photocell is optional. The fixture is Black. Color is adjustable with onboard toggle: 3000K or 4000K or 5000K.

Fixture is equipped with a 100V-277V voltage LED Driver. It can dim as well: 1-10V. This fixture includes a slip fitter bracket that can be mounted on a 3 pole. It is rated for Wet locations and is IP65 rated. They can operate in temperatures ranging -40 F to 113 F.

### Product Specifications

<b>Watts:</b>	30   50   60	<b>Dimmable:</b>	1-10V
<b>Lumens:</b>	3600   6000   7200	<b>Beam Angle:</b>	Type 5
<b>Lumens/Watt:</b>	120	<b>Optics:</b>	Frosted Tempered Glass
<b>Replaces:</b>	250 Watt Metal Halide	<b>Frequency:</b>	50-60Hz
<b>Color Temp:</b>	3000K   4000K   5000K	<b>Power Factor:</b>	> .90
<b>CRI:</b>	70+	<b>THD:</b>	< 20%
<b>IP Rating:</b>	IP65	<b>Housing:</b>	Die-Cast Aluminum
<b>Input Voltage:</b>	100V-277V	<b>Fixture Color:</b>	Black
<b>Operating Temp:</b>	-40°F to +113°F	<b>Mounting:</b>	3 in Pole
<b>Rated Life:</b>	50,000 (L70) hours	<b>EPA Rating:</b>	1.2
		<b>Dimensions:</b>	11.9 in X 11.9 in X 26 in
		<b>Warranty:</b>	5 years

## 30 / 50 / 100 Watt LED Decorative Post Top Fixture | 3600 to 13000 Lumens



### Product Details

**SKU:** MLLG-YA-LED-PTD-100-CC

**Web ID:** 2154

30 | 50 | 100 Watt Changing Decorative LED post top fixture produces 3600 | 6000 | 13000 lumens at LM/W replacing 250 | 400 Watt Metal Halide. The fixture has a 360 degree beam angle. Photocell is optional. The fixture is Black. Color is adjustable with onboard toggle: 3000K or 4000K or 5000K.

Fixture is equipped with a 100V-277V voltage LED Driver. It can dim as well: 1-10V. This fixture includes a slip fitter bracket that can be mounted on a 3 pole. It is rated for Wet locations and is IP65 rated. They can operate in temperatures ranging -40 F to 113 F.

### Product Specifications

<b>Watts:</b>	30   50   100	<b>Dimmable:</b>	1-10V
<b>Lumens:</b>	3600   6000   13000	<b>Beam Angle:</b>	Type 5
<b>Replaces:</b>	250   400 Watt Metal Halide	<b>Optics:</b>	Frosted Tempered Glass
<b>Color Temp:</b>	3000K   4000K   5000K	<b>Frequency:</b>	50-60Hz
<b>CRI:</b>	70+	<b>Power Factor:</b>	> .90
<b>IP Rating:</b>	IP65	<b>THD:</b>	< 20%
<b>Input Voltage:</b>	100V-277V	<b>Housing:</b>	Die-Cast Aluminum
<b>Operating Temp:</b>	-40°F to +113°F	<b>Fixture Color:</b>	Black
<b>Rated Life:</b>	50,000 (L70) hours	<b>Mounting:</b>	3 in Pole
		<b>EPA Rating:</b>	1.2
		<b>Dimensions:</b>	11.9 in X 11.9 in X 26 in
		<b>Warranty:</b>	5 years

## 80 / 100 / 120 Watt LED Decorative Post Top Fixture | 9600 to 14400 Lumens



### Product Details

**SKU:** MLLG-YA-LED-PTD-120-CC

**Web ID:** 2059

80 | 100 | 120 Watt Changing Decorative LED post top fixture produces 9600 | 12000 | 14400 lumens at 120 LM/W replacing 400 Watt Metal Halide. The fixture has a 360 degree beam angle. Photocell is optional. The fixture is Black. Color is adjustable with onboard toggle: 3000K or 4000K or 5000K.

Fixture is equipped with a 100V-277V voltage LED Driver. It can dim as well: 1-10V. This fixture includes a slip fitter bracket that can be mounted on a 3 pole. It is rated for Wet locations and is IP65 rated. They can operate in temperatures ranging -40 F to 113 F.

### Product Specifications

<b>Watts:</b>	80   100   120	<b>Dimmable:</b>	1-10V
<b>Lumens:</b>	9600   12000   14400	<b>Beam Angle:</b>	Type 5
<b>Lumens/Watt:</b>	120	<b>Optics:</b>	Frosted Tempered Glass
<b>Replaces:</b>	400 Watt Metal Halide	<b>Frequency:</b>	50-60Hz
<b>Color Temp:</b>	3000K   4000K   5000K	<b>Power Factor:</b>	> .90
<b>CRI:</b>	70+	<b>THD:</b>	< 20%
<b>IP Rating:</b>	IP65	<b>Housing:</b>	Die-Cast Aluminum
<b>Input Voltage:</b>	100V-277V	<b>Fixture Color:</b>	Black
<b>Operating Temp:</b>	-40°F to +113°F	<b>Mounting:</b>	3 in Pole
<b>Rated Life:</b>	50,000 (L70) hours	<b>EPA Rating:</b>	1.2
		<b>Dimensions:</b>	11.9 in X 11.9 in X 26 in
		<b>Warranty:</b>	5 years