



Commercial Lighting



Industrial Lighting



Sports Lighting

MLLG-YA-LED-WPFCD Wall Pack Product Family



**Why
contractors
choose us**



Free Lighting
Plans to ensure
customer
satisfaction



Dedicated
Lighting
Specialist for
each project



Large
inventory of
LED Lights

Table of Contents

	Page Number
- MLLG-YA-LED-WPFCD-24-50	3
- MLLG-YA-LED-WPFCD-48-50	4
- MLLG-YA-LED-WPFCD-80-50	5
- MLLG-YA-LED-WPFCD-100-50	6

24 Watt LED Full Cutoff Wall Pack | 3100 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-YA-LED-WPFC-D-24-50

Web ID: 1813

24 Watt full-cutoff wall pack produces 3100 lumens at 129 lumens/watt and replaces 100 Watt Metal Halide. It has a die-cast aluminum housing and an impact-resistant polycarbonate lens. Its the perfect replacement for metal halide outdoor wall packs.

This wall pack offers 5000K color temperature and 100V-277V LED Driver. The housing makes quick and easy installation with a removable hinge door and multiple points of entry. They are IP65 wet location rated.

Product Specifications

Watts:	24	Frequency:	50-60Hz
Lumens:	3100	Power Factor:	> .90
Lumens/Watt:	129	THD:	< 20%
Replaces:	100 Watt Metal Halide	Housing:	Powder Coated Die-Cast Aluminum with Polycarbonate Lens
Color Temp:	5000K	Fixture Color:	Bronze
CRI:	70+	Mounting:	Wall
IP Rating:	IP65	Dimensions:	11.7 in L x 3.6 in W x 8.6 in D
Input Voltage:	100V-277V	Warranty:	5 years
Operating Temp:	-40°F to +113°F		
Rated Life:	50,000 (L70) hours		

48 Watt LED Full Cutoff Wall Pack | 6400 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-YA-LED-WPFC48-50

Web ID: 1814

48 Watt full-cutoff wall pack produces 6400 lumens at 133 lumens/watt and replaces 150 Watt Metal Halide. It has a die-cast aluminum housing and an impact-resistant polycarbonate lens. Its the perfect replacement for metal halide outdoor wall packs.

This wall pack offers 5000K color temperature and 100V-277V LED Driver. The housing makes quick and easy installation with a removable hinge door and multiple points of entry. They are IP65 wet location rated.

Product Specifications

Watts:	48	Frequency:	50-60Hz
Lumens:	6400	Power Factor:	> .90
Lumens/Watt:	133	THD:	< 20%
Replaces:	150 Watt Metal Halide	Housing:	Powder Coated Die-Cast Aluminum with Polycarbonate Lens
Color Temp:	5000K	Fixture Color:	Bronze
CRI:	70+	Mounting:	Wall
IP Rating:	IP65	Dimensions:	11.7 in L x 3.6 in W x 8.6 in D
Input Voltage:	100V-277V	Warranty:	5 years
Operating Temp:	-40°F to +113°F		
Rated Life:	50,000 (L70) hours		

80 Watt LED Full Cutoff Wall Pack | 10300 Lumens | 5000K | 100-277V

Product Details

SKU: MLLG-YA-LED-WPFCD-80-50

Web ID: 1815

80 Watt full-cutoff wall pack produces 10300 lumens at 129 lumens/watt and replaces 250 Watt Metal Halide. It has a die-cast aluminum housing and an impact-resistant polycarbonate lens. Its the perfect replacement for metal halide outdoor wall packs.

This wall pack offers 5000K color temperature and 100V-277V LED Driver. The housing makes quick and easy installation with a removable hinge door and multiple points of entry. They are IP65 wet location rated.



Product Specifications

Watts:	80	Frequency:	50-60Hz
Lumens:	10300	Power Factor:	> .90
Lumens/Watt:	129	THD:	< 20%
Replaces:	250 Watt Metal Halide	Housing:	Powder Coated Die-Cast Aluminum with Polycarbonate Lens
Color Temp:	5000K	Fixture Color:	Bronze
CRI:	70+	Mounting:	Wall
IP Rating:	IP65	Dimensions:	11.7 in L x 3.6 in W x 8.6 in D
Input Voltage:	100V-277V	Warranty:	5 years
Operating Temp:	-40°F to +113°F		
Rated Life:	50,000 (L70) hours		

100 Watt LED Full Cutoff Wall Pack | 12900 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-YA-LED-WPFC-D-100-50

Web ID: 1816

100 Watt full-cutoff wall pack produces 12900 lumens at 129 lumens/watt and replaces 250 Watt Metal Halide. It has die-cast aluminum housing and impact-resistant polycarbonate lens. Its the perfect replacement for metal halide outdoor wall packs.

This wall pack offers 5000K color temperature and 100V-277V LED Driver. The housing makes quick and easy installation with a removable hinge door and multiple points of entry. They are IP65 wet location rated.

Product Specifications

Watts:	100	Frequency:	50-60Hz
Lumens:	12900	Power Factor:	> .90
Lumens/Watt:	129	THD:	< 20%
Replaces:	250 Watt Metal Halide	Housing:	Powder Coated Die-Cast Aluminum with Polycarbonate Lens
Color Temp:	5000K	Fixture Color:	Bronze
CRI:	70+	Mounting:	Wall
IP Rating:	IP65	Dimensions:	11.7 in L x 3.6 in W x 8.6 in D
Input Voltage:	100V-277V	Warranty:	5 years
Operating Temp:	-40°F to +113°F		
Rated Life:	50,000 (L70) hours		