



Commercial Lighting



Industrial Lighting



Sports Lighting

MLLG-YA-LED-WPSC Wall Pack Product Family



**Why
contractors
choose us**



Free Lighting
Plans to ensure
customer
satisfaction



Dedicated
Lighting
Specialist for
each project



Large
inventory of
LED Lights

Table of Contents

	Page Number
- MLLG-YA-LED-WPSC-15-50	3
- MLLG-YA-LED-WPSC-24-50	4
- MLLG-YA-LED-WPSC-48-50	5
- MLLG-YA-LED-WPSC-90-50	6

15 Watt LED Semi Cutoff Wall Pack | 1950 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-YA-LED-WPSC-15-50

Web ID: 1772

15 Watt semi-cutoff wall pack produces 1950 lumens replacing 70 Watt Metal Halide at 130 lumens/watt and has die-cast aluminum housing and impact-resistant polycarbonate 120X90 lens.

Its the perfect replacement for metal halide outdoor semi-cutoff wall packs. -40 F to 113 F color temperature and 100V-277V LED Drivers. They are IP65 wet location rated.

Product Specifications

Watts:	15	Dimmable:	No
Lumens:	1950	Beam Angle:	120X90°
Lumens/Watt:	130	Frequency:	50-60Hz
Replaces:	70 Watt Metal Halide	Power Factor:	> .90
Color Temp:	5000K	THD:	< 20%
CRI:	70+	Housing:	Powder Coated Die-Cast Aluminum with Polycarbonate Lens
IP Rating:	IP65	Fixture Color:	Bronze
Input Voltage:	100V-277V	Mounting:	Wall
Operating Temp:	-40°F to +113°F	Dimensions:	7.72 L X 5.83 W X 6.54 H
Rated Life:	50,000 (L70) hours	Weight:	3.2
		Warranty:	5 years

24 Watt LED Semi Cutoff Wall Pack | 3210 Lumens | 5000K | 100-277V

Product Details

SKU: MLLG-YA-LED-WPSC-24-50

Web ID: 1773

24 Watt semi-cutoff wall pack produces 3120 lumens replacing 100 Watt Metal Halide at 130 lumens/watt and has die-cast aluminum housing and impact-resistant polycarbonate 120X90 lens.

Its the perfect replacement for metal halide outdoor semi-cutoff wall packs. -40 F to 113 F color temperature and 100V-277V LED Drivers. They are IP65 wet location rated.



Product Specifications

Watts:	24	Dimmable:	No
Lumens:	3120	Beam Angle:	120X90°
Lumens/Watt:	130	Frequency:	50-60Hz
Replaces:	100 Watt Metal Halide	Power Factor:	> .90
Color Temp:	5000K	THD:	< 20%
CRI:	70+	Housing:	Powder Coated Die-Cast Aluminum with Polycarbonate Lens
IP Rating:	IP65	Fixture Color:	Bronze
Input Voltage:	100V-277V	Mounting:	Wall
Operating Temp:	-40°F to +113°F	Dimensions:	7.72 L X 5.83 W X 6.54 H
Rated Life:	50,000 (L70) hours	Weight:	3.5
		Warranty:	5 years

48 Watt LED Semi Cutoff Wall Pack | 6240 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-YA-LED-WPSC-48-50

Web ID: 1774

48 Watt semi-cutoff wall pack produces 6240 lumens replacing 150 Watt Metal Halide at 130 lumens/watt and has die-cast aluminum housing and impact-resistant polycarbonate 120X90 lens.

Its the perfect replacement for metal halide outdoor semi-cutoff wall packs. -40 F to 113 F color temperature and 100V-277V LED Drivers. They are IP65 wet location rated.

Product Specifications

Watts:	48	Dimmable:	No
Lumens:	6240	Beam Angle:	120X90°
Lumens/Watt:	130	Frequency:	50-60Hz
Replaces:	150 Watt Metal Halide	Power Factor:	> .90
Color Temp:	5000K	THD:	< 20%
CRI:	70+	Housing:	Powder Coated Die-Cast Aluminum with Polycarbonate Lens
IP Rating:	IP65	Fixture Color:	Bronze
Input Voltage:	100V-277V	Mounting:	Wall
Operating Temp:	-40°F to +113°F	Dimensions:	7.72 L X 5.83 W X 6.54 H
Rated Life:	50,000 (L70) hours	Weight:	4
		Warranty:	5 years

90 Watt LED Wall Pack | 10118 Lumens | 5000K | 100-277V | Semi Cutoff



Product Details

SKU: MLLG-YA-LED-WPSC-90-50

Web ID: 1776

90 Watt semi-cutoff wall pack produces 10118 lumens replacing 250 Watt Metal Halide at 112 lumens/watt and has die-cast aluminum housing and impact-resistant polycarbonate 120X90 lens.

Its the perfect replacement for metal halide outdoor semi-cutoff wall packs. -40 F to 113 F color temperature and 100V-277V LED Drivers. They are IP65 wet location rated.

Product Specifications

Watts:	90	Dimmable:	No
Lumens:	10118	Beam Angle:	120X90°
Lumens/Watt:	112	Frequency:	50-60Hz
Replaces:	250 Watt Metal Halide	Power Factor:	> .90
Color Temp:	5000K	THD:	< 20%
CRI:	70+	Housing:	Powder Coated Die-Cast Aluminum with Polycarbonate Lens
IP Rating:	IP65	Fixture Color:	Bronze
Input Voltage:	100V-277V	Mounting:	Wall
Operating Temp:	-40°F to +113°F	Dimensions:	10.71 in L X 8.39 in W X 8.78 in H
Rated Life:	50,000 (L70) hours	Weight:	9
		Warranty:	5 years